SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Product name: GDi Induction System Cleaner

• **Part number:** 400-2425

- · Application of the substance / the mixture engine system cleaner
- 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: CPS Products Inc. - USA

1010 E 31st Street Hialeah, FL 33013 USA Tel: (305) 687-4121 email of person responsible: cs@cpsproducts.com • email of person responsible: cs@cpsproducts.com

· 1.4 Emergency telephone number: CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226 Flammable liquid and vapour.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

(R)-p-mentha-1,8-diene

- · Hazard statements
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

- GB

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

(Contd. of page 1)

P264 Wash thoroughly after handling. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents in accordance with local regulations.

· 2.3 Other hazards

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Chemical compo	onents:	
CAS: 1330-20-7 EINECS: 215-535-7	xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol	
CAS: 5989-27-5 EINECS: 227-813-5	(R)-p-mentha-1,8-diene Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	10-25%
CAS: 108-11-2 EINECS: 203-551-7	4-methylpentan-2-ol Flam. Liq. 3, H226; STOT SE 3, H335	2.5-10%
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304	≤2.5%
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226; Asp. Tox. 1, H304	≤2.5%
CAS: 91-20-3 EINECS: 202-049-5	naphthalene Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≤2.5%
· Other Ingredient	ts	
CAS: 64742-46-7 EINECS: 265-148-2	Distillates (petroleum), hydtrotreated middle Asp. Tox. 1, H304	≤2.5%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≤2.5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
 - After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

GB

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

After swallowing: DO NOT INDUCE VOMITING. Get immediate medical attention.

· Information for doctor: Treat Symptomatically

4.2 Most important symptoms and effects, both acute and delayed

May cause eye irritation. Symptons may include discomfort or pain, excessive blinking and tear production, with possible redness and swelling.

Headache

Dizziness

Disorientation

Nausea

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

4.3 Indication of any immediate medical attention and special treatment needed

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

SECTION 5: Firefighting measures

[·] 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture See section 10 for additional information.

5.3 Advice for firefighters

Protective equipment:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

SECTION 6: Accidental release measures

- $^{\circ}$ 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

(Contd. on page 4)

GB

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

(Contd. of page 3)

Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

· 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

- Prevent formation of aerosols.
 - Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect from heat. Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
 - Requirements to be met by storerooms and receptacles: See section 10 for incompatible materials.
 - · Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions:
 - Keep container tightly sealed.
 - Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene (10-25%) WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

111-76-2 2-butoxyethanol (10-25%)

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

108-11-2 4-methylpentan-2-ol (≤10%)

WEL Short-term value: 170 mg/m³, 40 ppm Long-term value: 106 mg/m³, 25 ppm Sk

(Contd. on page 5)

Safety data sheet

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

	(Contd. of pag				
	Ingredients with biological limit values:				
1330-20-7 xylene (10-25%)					
BMGV	650 mmol/mol creatinine Octanol-Water: urine 0.1: post shift 7.3: methyl hippuric acid				
111_76.					
BMGV	111-76-2 2-butoxyethanol (10-25%) BMGV 240 mmol/mol creatinine Octanol-Water: urine 0.1: post shift 7.3: butoxyacetic acid				
· A	Additional information: The lists valid during the making were used as basis.				
lr A • R Ir Ic	Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Avoid contact with the eyes and skin. Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive longer exposure use self-contained respiratory protective device. Protection of hands:				
·E	Eye protection:				
	Safety glasses. If potential for splash or mist exists, wear chemical goggles faceshield.				
SECT	FION 9: Physical and chemical properties				
	ormation on basic physical and chemical properties neral Information Appearance:				
· Gen	, have see				
· Gen	· Form: Liquid				
· Gen	· Form: Liquid · Colour: Amber coloured				
·Gen ·A	Colour: Amber coloured Odour: Citrus				
·Gen ·A	Colour: Amber coloured				
Gen	Colour: Amber coloured Odour: Citrus				
Gen A C PH-\ Cha N	Colour: Amber coloured Odour: Citrus Odour threshold: Not determined.				

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

	(Contd. of page 5		
· Flash point:	28 °C		
· Flammability (solid, gas):	Not applicable.		
 Decomposition temperature: 	Not determined.		
· Auto-ignition temperature:	Product is not selfigniting.		
• Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
· Explosion limits:			
· Lower:	Not determined.		
· Upper:	Not determined.		
· Vapour pressure:	Not determined.		
· Density:	Not determined.		
Relative density at 20 °C	0.84-0.88		
· Vapour density	Not determined.		
• Evaporation rate	Not determined.		
 Solubility in / Miscibility with 			
· water:	Not miscible or difficult to mix.		
· Partition coefficient: n-octanol/v	· Partition coefficient: n-octanol/water: Not determined.		
· Viscosity:			
· Dynamic:	Not determined.		
· Kinematic:	Not determined.		
• 9.2 Other information	No further relevant information available.		

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

- 10.2 Chemical stability
 - Thermal decomposition / conditions to be avoided:
 - Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Heat, open flames, sparks.
- · 10.5 Incompatible materials:

Strong Oxidizers acids

- · 10.6 Hazardous decomposition products:
- Nitrogen oxides

Ammonia

May include, and are not limited to: oxides of carbon.

- aliphatic alcohols
- polyalkylglycols
- Propylamine

(Contd. on page 7)

GB

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

(Contd. of page 6)

SECTIO	N 11: Toxicolo	ogical information			
	mation on toxico				
	· Acute toxicity Based on available data, the classification criteria are not met.				
	· LD/LC50 values relevant for classification:				
•	te Toxicity Estim	•			
Oral	LD50	3,303 mg/kg			
Dermal	LD50	2,842 mg/kg			
Inhalative	LC50/4 h (vapor)	68.7 mg/L (gpg)			
1330-20-7	xylene				
Oral	LD50	4,300 mg/kg (rat)			
Dermal	LD50	2,000 mg/kg (rabbit)			
Inhalative	LC50/4 h (vapor)	6,700 mg/L (rat)			
	2-butoxyethanol				
Oral	LD50	1,414 mg/kg (gpg)			
Dermal	LD50	2,000 mg/kg (gpg)			
	LC50/4 h (vapor)				
5989-27-5	(R)-p-mentha-1,	B-diene			
Oral	LD50	4,400 mg/kg (rat)			
Dermal	LD50	>5 g/Kg (rabbit)			
	4-methylpentan-2				
Oral	LD50	2,590 mg/kg (rat)			
Dermal	LD50	3,560 mg/kg (rabbit)			
	aphthalene				
Oral	LD50	490 mg/kg (rat)			
Dermal	LD50	5,000 mg/kg (rat)			
	nary irritant effec				
	Skin corrosion/irı Causes skin irritati				
	Serious eye dama				
(Causes serious ey	e irritation.			
	Inhalation: May cause respiratory tract irritation.				
	 Ingestion: May be fatal if swallowed and enter airways. Respiratory or skin sensitisation 				
	May produce an allergic reaction. May cause an allergic skin reaction.				
· Additio	onal toxicologica	l information:			
		ogenity, mutagenicity and toxicity for reproduction)			
		nicity Based on available data, the classification criteria are not met.			
	• Carcinogenicity Based on available data, the classification criteria are not met.				
		icity Based on available data, the classification criteria are not met. Ire Based on available data, the classification criteria are not met.			
		osure Based on available data, the classification criteria are not met.			

STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Issue date: 23.03.2022

Version 3

Product name: GDi Induction System Cleaner

(Contd. of page 7)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

• Aquatic toxicity:

5989-27-5 (R)-p-mentha-1,8-diene

LC50 (96 h) 0.619-0.796 mg/L (Pimephales promelas)

12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential

108-11-2 4-methylpentan-2-ol

Bioaccumulation 1.43 (-) (potential low)

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Toxic for fish

· Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

12.6 Other adverse effects Avoid release to the environment.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number ADR, IMDG, IATA

UN1993

(Contd. on page 9)

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

	(Contd. of page
 14.2 UN proper shipping name ADR 	UN1993 FLAMMABLE LIQUID, N.O.S (XYLENES, DIPENTENE, METHYL ISOBUTY
·IMDG	CARBINOL, 2-butoxyethanol) FLAMMABLE LIQUID, N.O.S. (XYLENES DIPENTENE, METHYL ISOBUTYL CARBINOL) MARINE POLLUTANT
	FLAMMABLE LIQUID, N.O.S. (XYLENES DIPENTENE, METHYL ISOBUTYL CARBINOL)
· 14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
· Label · IMDG, IATA	3
· Class · Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
	Product contains environmentally hazardou substances: (R)-p-mentha-1,8-diene
	Warning: Flammable liquids.
 Hazard identification number (Kemler cod · EMS Number; 	de): 30 F-E,S-E
Stowage Category	A
 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1
	Maximum net quantity per inne packaging: 30 ml
· Transport category	Maximum net quantity per oute packaging: 1000 ml 3
	(Contd. on page 1

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

	(Contd. of page 9)
 Tunnel restriction code 	D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, DIPENTENE, METHYL ISOBUTYL CARBINOL, 2-BUTOXYETHANOL), 3, I

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No GB REACH Annex XVII restrictions Contains no GB REACH candidate substance

- · Directive 2012/18/EU
 - Named dangerous substances ANNEX I None of the ingredients is listed.
 - Seveso category
 - E2 Hazardous to the Aquatic Environment
 - P5c FLAMMABLE LIQUIDS
 - \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
 - · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Issue Date: 14/FEB/2017
- · Contact: Engineering Department
- · Issue Date 02.08.2016
- Revision Changes:
- v 1.0 original SDS release (13/OCT/2015)
- v 2.0 revised (02/AUG/2016)
- v 3.0 revised section 2&3 (14/FEB/2017)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

(Contd. on page 11)

Issue date: 23.03.2022

Version 3

Last Revision: 02.08.2016

Product name: GDi Induction System Cleaner

(Contd. of page 10)

GB

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2