Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

1 Identification

- · Product identifier
 - · Trade name: Engine Oil Cleaner
 - · Part number: 400-5000EU, 400-5000
 - · Application of the substance / the mixture Engine oil flush
- Details of the supplier of the safety data sheet

CPS Product Inc. - USA 1010 East 31st Street Hialeah, FL 33013 USA Phone: (305) 687 - 4121 Email: cs@cpsproducts.com Manufacturer/Supplier:

Manufacturer/Supplier: CPS Product Inc - USA 1010 East 31st Street Hialeah, FL 33013 USA

Contact Phone: (305) 687-4121

- email of person responsible: cs@cpsproducts.com
- **Emergency telephone number:**

CHEMTREC International +1 (703) 527-3887 (outside the US), 1-800-424-9300 (in the US) 24 hr

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 3 H226 Flammable liquid and vapor.

Acute Toxicity - Oral 4 H302 Harmful if swallowed.

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.
Skin Irrititation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







- · Signal word Warning
- · Hazard-determining components of labeling:

2-butoxyethanol

(R)-p-mentha-1,8-diene

Hazard statements

Flammable liquid and vapor.

Harmful if swallowed.

(Contd. on page 2)

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

(Contd. of page 1)

Harmful in contact with skin.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If skin irritation or rash occurs: Get medical attention.

Store in a well-ventilated place. Keep cool.

Dispose of contents in accordance with local regulations.

Other hazards

· **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Chemic	Chemical components:	
111-76-2	2-butoxyethanol	25-50%
5989-27-5	(R)-p-mentha-1,8-diene	25-50%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Wash with plenty of soap and water. Remove contaminated clothing. If skin irritation occurs, get medical attention. Launder contaminated clothing before reuse.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor: Treat Symptomatically

(Contd. on page 3)

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

(Contd. of page 2)

· Most important symptoms and effects, both acute and delayed

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause respiratory tract irritation.

See section 11.

· Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
 - Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture See section 10 for additional information.
- Advice for firefighters
 - · Protective equipment:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

NA

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

(Contd. of page 3)

7 Handling and storage

- · Handling:
 - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - Requirements to be met by storerooms and receptacles:

See section 10 for incompatible materials.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol (25-50%)

	TWA: 240 mg/m³, 50 ppm Skin
REL (USA)	TWA: 24 mg/m³, 5 ppm Skin
TLV (USA)	TWA: 20 ppm BEI, A3 TWA: 20 ppm TWA: 20 ppm
EL (Canada)	TWA: 20 ppm
EV (Canada)	TWA: 20 ppm Skin

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol (25-50%)

BEI (USA) 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
 - · Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

· Breathing equipment:

(Contd. of page 4)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:





Chemical resistant protective gloves

· Eye protection:



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

· Body protection: Protective work clothing

9 Physical and chemical properties	
· Information on basic physical and che	mical properties
General Information	• •
· Appearance:	
· Form:	Fluid
· Color:	Amber colored
· Odor:	Citrus
· Odor threshold:	Not determined.
· pH-value at 20 °C:	4
· Change in condition	
 Melting point/Melting range: 	Undetermined.
 Boiling point/Boiling range: 	171 °C
· Flash point:	53 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	0.7 Vol %
· Upper:	10.6 Vol %
· Vapor pressure at 20 °C:	2.3 hPa
· Density at 20 °C:	0.87 g/cm³
· Relative density	Not determined.
· Vapor density	Not determined.
	(Contd. on page 6)

(Contd. on page 6)

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

		(Contd. of page 5
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with · Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 40 °C:	1.77 mm²/s	
· Solvent separation test		
VOC content:	60.00 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
 - Thermal decomposition / conditions to be avoided:
 Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, open flames, sparks.
- · Incompatible materials: Strong Oxidizers, strong acids.
- · Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

11 Toxicological information

- · Information on toxicological effects
 - Acute toxicity:

· Acute	· Acute toxicity:				
· LD/	· LD/LC50 values that are relevant for classification:				
ATE (Acu	ATE (Acute Toxicity Estimate)				
Oral	LD50	4,000 mg/kg			
Dermal	LD50	6,667 mg/kg (gpg)			
Inhalative	Inhalative LC50/4 h (vapor) 38.3 mg/L (gpg)				
111-76-2 2	111-76-2 2-butoxyethanol				
Oral	LD50	1,200 mg/kg (ATE)			
		1,414 mg/kg (gpg)			
Dermal	LD50	2,000 mg/kg (gpg)			
Inhalative	LC50/4 h (vapor)	11.5 mg/L (gpg)			
5989-27-5	5989-27-5 (R)-p-mentha-1,8-diene				
Oral	LD50	4,400 mg/kg (rat)			
Dermal	LD50	>5 g/Kg (rabbit)			
D.:	Drimany irritant affacts				

- · Primary irritant effect:
 - · on the skin: Irritant to skin and mucous membranes.
 - · on the eye: Irritating effect.

(Contd. on page 7)

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

(Contd. of page 6)

· Ingestion:

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

· Sensitization:

May produce an allergic reaction.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

IARC (International Agency for Research on Cancer)

All components have the value 3.

NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
 - · Aquatic toxicity:

5989-27-5 (R)-p-mentha-1,8-diene

LC50 (96 h) 0.619-0.796 mg/L (Pimephales promelas)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Very toxic for fish
- Additional ecological information:
 - General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- Other adverse effects Avoid release to the environment.

۱A

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· EMS Number:

· Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number	
· DOT · ADR, IMDG, IATA	UN1993 UN2052
· · · · · · · · · · · · · · · · · · ·	UNZUJZ
UN proper shipping name DOT	Flammable liquids, n.o.s. (Dipentene
DO 1	butoxyethanol)
· IMDG	DIPENTENE solution, MARINE POLLUTANT
· IATA	DIPENTENE solution
Transport hazard class(es)	
· DOT	
RAMMARE LIQUO	
· Class · Label	3 Flammable liquids 3
· IMDG, IATA	
3	
· Class	3 Flammable liquids
· Label	3
Packing group · DOT, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazard substances: (R)-p-mentha-1,8-diene
· Marine pollutant:	Yes

F-E,S-E

(Contd. on page 9)

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

	(Contd. of page 8
· Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging 1000 ml
· UN "Model Regulation":	UN 2052 DIPENTENE SOLUTION, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No REACH Annex XVII restrictions
 Contains no REACH candidate substance
 - Sara
 - Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- · Proposition 65
 - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories
 - · EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

NL

· TLV (Threshold Limit Value)

111-76-2 2-butoxyethanol

A3

(Contd. on page 10)

Issue date: 23.03.2022 v 5 Last Revision Date: 23.03.2022

Trade name: Engine Oil Cleaner

(Contd. of page 9)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact: Engineering Department
 - · Issue Date

23.03.2022

2015/06/26

- · Revision Changes:
- v 1.0 original SDS release (2015/06/26)
- v 2.0 modified product name field (2015/07/13)
- v 3.0 modified transportation section (2015/09/17)
- v 4.0 modified shipping number (2016/08/31)
- Abbreviations and acronyms:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Flammable Liquids 3: Flammable liquids - Category 3

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Skin 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.