Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

#### 1 Identification

- · Product identifier
  - · Trade name: TerraDiesel Fuel Treatment
    - · Part number: 201245, 201248, 201249
    - · Application of the substance / the mixture diesel fuel additive
- Details of the supplier of the safety data sheet

CPS Product Inc. - USA 1010 East 31st Street Hialeah, FL 33013 USA Phone: (305) 687 - 4121 Email: cs@cpsproducts.com

Manufacturer/Supplier: CPS Product Inc - USA 1010 East 31st Street Hialeah, FL 33013 USA

Contact Phone: (305) 687-4121

- email of person responsible: cs@cpsproducts.com
- · Emergency telephone number:

CHEMTREC International +1 (703) 527-3887 (outside the US), 1-800-424-9300 (in the US) 24 hr

### 2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 4 H227 Combustible liquid.
Acute Toxicity - Oral 4 H302 Harmful if swallowed.
Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.
Skin Irrititation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Aquatic Acute 3 H402 Harmful to aquatic life.

- · Label elements
  - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

2-butoxyethanol

2-ethylhexyl nitrate

· Hazard statements

Combustible liquid.

Harmful if swallowed.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Harmful to aquatic life.

(Contd. on page 2)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

### Trade name: TerraDiesel Fuel Treatment

(Contd. of page 1)

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical attention.

Dispose of contents in accordance with local regulations.

#### · Other hazards

PBT: Not applicable.vPvB: Not applicable.

#### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Chemica	al components:	
111-76-2	2-butoxyethanol	50-100%
104-76-7	2-Ethyl-1-hexanol	≤2.5%
112-80-1	oleic acid, pure	≤2.5%
27247-96-7	2-ethylhexyl nitrate	≤2.5%

<sup>•</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- Description of first aid measures
  - · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor: Treat Symptomatically
  - Most important symptoms and effects, both acute and delayed

Headache

Unconsciousness

Nausea

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause respiratory tract irritation.

blurred vision

See section 11.

(Contd. on page 3)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

#### Trade name: TerraDiesel Fuel Treatment

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **5 Fire-fighting measures**

- · Extinguishing media
  - Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture See section 10 for additional information.
- Advice for firefighters
  - · Protective equipment:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

#### **6 Accidental release measures**

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
  - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Personal protective equipment must be worn. Avoid contact with skin, eyes or clothing.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep away from ignition sources and high temperature materials.

- · Conditions for safe storage, including any incompatibilities
  - · Storage:
    - Requirements to be met by storerooms and receptacles:

See section 10 for incompatible materials.

(Contd. on page 4)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

### Trade name: TerraDiesel Fuel Treatment

(Contd. of page 3)

- Information about storage in one common storage facility:
  - Store at temperatures not exceeding 49°C/120°F.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Keep from freezing.

· Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

#### · Control parameters

#### 111-76-2 2-butoxyethanol (50-100%)

PEL (USA) TWA: 240 mg/m³, 50 ppm

Skin

REL (USA) TWA: 24 mg/m<sup>3</sup>, 5 ppm

Skin

TLV (USA) TWA: 20 ppm

BEI, A3

EL (Canada) TWA: 20 ppm

EV (Canada) TWA: 20 ppm

Skin

### · Ingredients with biological limit values:

#### 111-76-2 2-butoxyethanol (50-100%)

BEI (USA) 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

#### · Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Protection of hands:





Chemical resistant protective gloves

(Contd. on page 5)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

# Trade name: TerraDiesel Fuel Treatment

# · Eye protection:

(Contd. of page 4)



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

9 Physical and chemical propertie	es	
Information on basic physical and che General Information Appearance:	emical properties	
Form:	Liquid	
· Color:	Amber colored	
· Odor:	Sweetish	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
<u> </u>		
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> </ul>	-70.4 °C	
Boiling point/Boiling range:	-70.4 C 171 °C	
<u> </u>		
· Flash point:	63 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
· Lower:	1.1 Vol %	
· Upper:	10.6 Vol %	
· Vapor pressure at 20 °C:	1.2 hPa	
· Density at 20 °C:	0.9 g/cm <sup>3</sup>	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water at 20 °C:	1 g/l	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic:	Not determined.	
		(Contd. on page 6)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

### Trade name: TerraDiesel Fuel Treatment

(Contd. of page 5)

· Solvent separation test

• **VOC content:** 97.00 %

• Other information No further relevant information available.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
  - · Thermal decomposition / conditions to be avoided:

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Heat, open flames, sparks.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

# 11 Toxicological information

- · Information on toxicological effects
  - · Acute toxicity:

· LD/	· LD/LC50 values that are relevant for classification:		
ATE (Acu	ATE (Acute Toxicity Estimate)		
Oral	LD50	1,232 mg/kg	
Dermal	LD50	1,232 mg/kg 2,023 mg/kg	
Inhalative	LC50/4 h (vapor)	12 mg/L	
111-76-2	2-butoxyethanol		
Oral	LD50	1.200 mg/kg (ATE)	

	2-Ethyl-1-hovanol	
Inhalative	LC50/4 h (vapor)	1,200 mg/kg (ATE) 1,414 mg/kg (gpg) 2,000 mg/kg (gpg) 11.5 mg/L (gpg)
Dermal	LD50	2,000 mg/kg (gpg)
		1,414 mg/kg (gpg)
Oral	LD50	1,200 mg/kg (ATE)

### 104-76-7 2-Ethyl-1-hexanol

Oral	LD50	2,049 mg/kg (rat)
Dermal	LD50	1,970 mg/kg (rabbit)

### 112-80-1 oleic acid, pure

Oral	LD50	74,000 mg/kg (rat	()
00040	<b>-</b> 41 11	 	

### 27247-96-7 2-ethylhexyl nitrate

Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h (vapor)	11 mg/L (ATE)

- Primary irritant effect:
  - · on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
  - · Inhalation: May cause respiratory tract irritation.

(Contd. on page 7)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

### Trade name: TerraDiesel Fuel Treatment

(Contd. of page 6)

- · Ingestion: May cause gastrointestinal irritation, nausea, vomiting, diarrhea.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

#### · IARC (International Agency for Research on Cancer)

111-76-2 2-butoxyethanol

3

#### NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
  - · Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

#### 112-80-1 oleic acid, pure

LC50 (96 h) 205 mg/L (fish)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
  - · Bioaccumulative potential

### 112-80-1 oleic acid, pure

Bioaccumulation 7.73 (-) (potential high)

- Mobility in soil No further relevant information available.
- · Additional ecological information:
  - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
  - · **PBT**: Not applicable.
  - · **vPvB:** Not applicable.
- · Other adverse effects Avoid release to the environment.

### 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

# Trade name: TerraDiesel Fuel Treatment

(Contd. of page 7)

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number	
· DOT, ADR, IMDG, IATA	Not Regulated
·TDG	UN2810
UN proper shipping name	
· DOT, IMDG, IATA	Not Regulated
· TDG	Toxic, liquids, organic, n.o.s. (2-butoxyethanol)
Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	Not Regulated
·TDG	
· Class	6.1 Toxic Substances
· Label	6.1
Packing group	
· DOT, IMDĠ, IATA	Not Regulated
TDG	III
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not Regulated

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No REACH Annex XVII restrictions

Contains no REACH candidate substance

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 9)

Issue date: 06.04.2022 v 1 Last Revision Date: 06.04.2022

### Trade name: TerraDiesel Fuel Treatment

(Contd. of page 8)

#### · Proposition 65

#### · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### · Carcinogenic categories

#### EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

NL

#### · TLV (Threshold Limit Value)

111-76-2 2-butoxyethanol

А3

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

#### · Canadian substance listings:

#### · Canadian Domestic Substances List (DSL)

All ingredients are listed.

#### · Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

#### · Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

#### · Canadian Ingredient Disclosure list (limit 1%)

111-76-2 2-butoxyethanol

104-76-7 2-Ethyl-1-hexanol

112-80-1 oleic acid, pure

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Contact:

Engineering Department Engineering Department

· Issue Date

06.04.2022

August 19, 2015

· Revision Changes: v 1.0 - original SDS release (August 19, 2015)

### · Abbreviations and acronyms:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

Last Revision Date: 06.04.2022 Issue date: 06.04.2022 v 1

# Trade name: TerraDiesel Fuel Treatment

(Contd. of page 9)

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Oral 4: Acute toxicity - Category 4
Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

\* Data compared to the previous version altered.