

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

## 1 Identification

- **Product identifier**

- **Trade name: TerraDiesel Multi-function Fuel Treatment**
- **Part number:** 201251, 201253, 201254, 201250
- **Application of the substance / the mixture** Diesel fuel additive

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

CPS Products Inc.  
1010 East 31st Street  
Hialeah,  
Florida 33013 USA  
Phone: (305) 687- 4121

- **email of person responsible:** cs@cpsproducts.com

- **Emergency telephone number:**

CHEMTREC International +1 (703) 527-3887 (outside the US), 1-800-424-9300 (in the US) 24 hr

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 3	H226 Flammable liquid and vapor.
Acute Toxicity - Oral 4	H302 Harmful if swallowed.
Acute Toxicity - Dermal 4	H312 Harmful in contact with skin.
Acute Toxicity - Inhalation 4	H332 Harmful if inhaled.
Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Germ Cell Mutagenicity 1B	H340 May cause genetic defects.
Carcinogenicity 1B	H350 May cause cancer.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



- **Signal word** Danger

- **Hazard-determining components of labeling:**

2-butoxyethanol  
Distillates (petroleum), hydrotreated light  
Solvent naphtha (petroleum), light arom.  
2-ethylhexyl nitrate

- **Hazard statements**

Flammable liquid and vapor.  
Harmful if swallowed.  
Harmful in contact with skin.

(Contd. on page 2)

NA

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 1)

Harmful if inhaled.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause genetic defects.  
 May cause cancer.  
 May be fatal if swallowed and enters airways.  
 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If swallowed: Immediately call a poison center/doctor.  
 Do NOT induce vomiting.  
 IF exposed or concerned: Get medical advice/attention.  
 Store in a well-ventilated place. Keep cool.  
 Dispose of contents in accordance with local regulations.

· **Other hazards**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**· **Chemical characterization: Mixtures**· **Chemical components:**

64742-47-8	Distillates (petroleum), hydrotreated light	25-50%
111-76-2	2-butoxyethanol	10-<25%
27247-96-7	2-ethylhexyl nitrate	10-<25%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-<10%
95-63-6	1,2,4-trimethylbenzene	0.1-≤2.5%
1330-20-7	xylene	0.1-≤2.5%
108-67-8	mesitylene	0.1-≤2.5%
91-20-3	naphthalene	0.1-≤2.5%
100-41-4	ethylbenzene	0.1-≤2.5%
102-25-0	1,3,5-triethylbenzene	0.1-≤2.5%
98-82-8	cumene	0.1-≤2.5%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	2.5-<10%
178535-25-6	Benzene, ethylenated, residues, distn. lights	0.1-<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**4 First-aid measures**· **Description of first aid measures**· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation continues, consult a doctor.

- **After eye contact:**

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- **After swallowing:** Do not induce vomiting; immediately call for medical help.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

- Headache

- Dizziness

- Disorientation

- Nausea

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

- **Indication of any immediate medical attention and special treatment needed**

Medical supervision for at least 48 hours.

**5 Fire-fighting measures**

- **Extinguishing media**

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water

- **Special hazards arising from the substance or mixture** See section 10 for additional information.

- **Advice for firefighters**

- **Protective equipment:**

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

NA

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 3)

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**7 Handling and storage**· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:**

See section 10 for incompatible materials.

· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **Specific end use(s)** No further relevant information available.**8 Exposure controls/personal protection**· **Control parameters**· **Components with limit values that require monitoring at the workplace:****64742-47-8 Distillates (petroleum), hydrotreated light (25-50%)**

EL (Canada)	TWA: 200 mg/m <sup>3</sup> Skin
-------------	------------------------------------

**111-76-2 2-butoxyethanol (10-<20%)**

PEL (USA)	TWA: 240 mg/m <sup>3</sup> , 50 ppm Skin
-----------	---

REL (USA)	TWA: 24 mg/m <sup>3</sup> , 5 ppm Skin
-----------	---

TLV (USA)	TWA: 97 mg/m <sup>3</sup> , 20 ppm BEI
-----------	---

EL (Canada)	TWA: 20 ppm
-------------	-------------

EV (Canada)	TWA: 20 ppm Skin
-------------	---------------------

**95-63-6 1,2,4-trimethylbenzene (≤2.5%)**

REL (USA)	TWA: 125 mg/m <sup>3</sup> , 25 ppm
-----------	-------------------------------------

(Contd. on page 5)

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 4)

TLV (USA)	TWA: 123 mg/m <sup>3</sup> , 25 ppm
<b>1330-20-7 xylene (1-&lt;2.5%)</b>	
PEL (USA)	TWA: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	STEL: 655 mg/m <sup>3</sup> , 150 ppm TWA: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	STEL: 651 mg/m <sup>3</sup> , 150 ppm TWA: 434 mg/m <sup>3</sup> , 100 ppm BEI
EL (Canada)	STEL: 150 ppm TWA: 100 ppm
EV (Canada)	STEL: 650 mg/m <sup>3</sup> , 150 ppm TWA: 435 mg/m <sup>3</sup> , 100 ppm
<b>108-67-8 mesitylene (0.1-&lt;2.5%)</b>	
REL (USA)	TWA: 125 mg/m <sup>3</sup> , 25 ppm
TLV (USA)	TWA: 123 mg/m <sup>3</sup> , 25 ppm
<b>91-20-3 naphthalene (0.25-&lt;1%)</b>	
PEL (USA)	TWA: 50 mg/m <sup>3</sup> , 10 ppm
REL (USA)	STEL: 75 mg/m <sup>3</sup> , 15 ppm TWA: 50 mg/m <sup>3</sup> , 10 ppm
TLV (USA)	TWA: 52 mg/m <sup>3</sup> , 10 ppm Skin; BEI
EL (Canada)	STEL: 15 ppm TWA: 10 ppm Skin; IARC 2B
EV (Canada)	STEL: 78 mg/m <sup>3</sup> , 15 ppm TWA: 52 mg/m <sup>3</sup> , 10 ppm
<b>· Ingredients with biological limit values:</b>	
<b>111-76-2 2-butoxyethanol (10-&lt;20%)</b>	
BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
<b>1330-20-7 xylene (1-&lt;2.5%)</b>	
BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

(Contd. on page 6)

-NA-

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 5)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Chemical resistant protective gloves

· **Eye protection:**

Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

· **Body protection:** Protective work clothing**9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

- **Form:** Liquid
- **Color:** Amber colored
- **Odor:** Petrol-like
- **Odor threshold:** Not determined.

· **pH-value:** Not determined.· **Change in condition**

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** Undetermined.

· **Flash point:** 45 °C· **Flammability (solid, gaseous):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

- **Lower:** Not determined.
- **Upper:** Not determined.

· **Vapor pressure:** Not determined.· **Density:** Not determined.

- **Relative density at 20 °C** 0.8-0.9
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.

(Contd. on page 7)

-NA

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 6)

· <b>Solubility in / Miscibility with</b>	
· <b>Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	Not determined.
· <b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
  - **Thermal decomposition / conditions to be avoided:**  
Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, open flames, sparks.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** May include, and are not limited to: oxides of carbon.

**11 Toxicological information**

- **Information on toxicological effects**
  - **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimate)</b>		
Oral	LD50	4902 mg/kg
Dermal	LD50	5443 mg/kg
Inhalative	LC50/4 h (vapor)	33.9 mg/L
<b>111-76-2 2-butoxyethanol</b>		
Oral	LD50	1414 mg/kg (gpg)
Dermal	LD50	2000 mg/kg (gpg)
Inhalative	LC50/4 h (vapor)	11.5 mg/L (gpg)
<b>27247-96-7 2-ethylhexyl nitrate</b>		
Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	1100 mg/kg (ATE)
Inhalative	LC50/4 h (vapor)	11 mg/L (ATE)
<b>64742-95-6 Solvent naphtha (petroleum), light arom.</b>		
Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h (vapor)	>10.2 mg/L (rat)

(Contd. on page 8)

NA

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

## Trade name: TerraDiesel Multi-function Fuel Treatment

(Contd. of page 7)

<b>95-63-6 1,2,4-trimethylbenzene</b>		
Oral	LD50	5000 mg/kg (rat)
Inhalative	LC50/4 h (vapor)	18 mg/L (rat)
<b>1330-20-7 xylene</b>		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h (vapor)	6700 mg/L (rat)
<b>178535-25-6 Benzene, ethylenated, residues, distn. lights</b>		
Oral	LD50	>2000 mg/kg (rat)
<b>91-20-3 naphthalene</b>		
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rat)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)
Inhalative	LC50/4 h (vapor)	17.8 mg/L (rat)
<b>98-82-8 cumene</b>		
Oral	LD50	1400 mg/kg (rat)
Dermal	LD50	12300 mg/kg (rabbit)
Inhalative	LC50/4 h (vapor)	24.7 mg/L (mouse)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic.

The product can cause inheritable damage.

· <b>IARC (International Agency for Research on Cancer)</b>		
111-76-2	2-butoxyethanol	3
1330-20-7	xylene	3
91-20-3	naphthalene	2B
100-41-4	ethylbenzene	2B
98-82-8	cumene	2B

· <b>NTP (National Toxicology Program)</b>		
91-20-3	naphthalene	R
98-82-8	cumene	R

· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

NA

(Contd. on page 9)



## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

Trade name: **TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 8)

**12 Ecological information**

- **Toxicity**
  - **Aquatic toxicity:** Harmful to aquatic life with long lasting effects.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
  - **Bioaccumulative potential** No further relevant information available.
  - **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
  - **Remark:** Harmful to fish
- **Additional ecological information:**
  - **General notes:**
    - Do not allow product to reach ground water, water course or sewage system.
    - Danger to drinking water if even small quantities leak into the ground.
    - Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.
  - **vPvB:** Not applicable.
- **Other adverse effects** Avoid release to the environment.

**13 Disposal considerations**

- **Waste treatment methods**
  - **Recommendation:**
    - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- |                                  |   |
|----------------------------------|---|
| · <b>UN-Number</b>               |   |
| · <b>DOT, ADR, IMDG, IATA</b>    | UN1993  |
| · <b>TDG</b>                     | UN1993  |
| · <b>UN proper shipping name</b> |   |
| · <b>DOT</b>                     | Flammable liquids, n.o.s. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light arom., Xylenes, 2-butoxyethanol) |
| · <b>TDG</b>                     | Flammable liquids, n.o.s. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light arom., Xylenes, 2-butoxyethanol) |
| · <b>IMDG, IATA</b>              | FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light arom., XYLENES, 2-butoxyethanol)  |

(Contd. on page 10)

-NA

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

## Trade name: TerraDiesel Multi-function Fuel Treatment

(Contd. of page 9)

## · Transport hazard class(es)

## · DOT



· Class 3 Flammable liquids  
 · Label 3

## · TDG

· Class 3 Flammable liquids  
 · Label 3

## · IMDG, IATA



· Class 3 Flammable liquids  
 · Label 3

## · Packing group

· DOT, IMDG, IATA III  
 · TDG III

## · Environmental hazards:

· Marine pollutant: No

## · Special precautions for user

Warning: Flammable liquids

· Hazard identification number (Kemler code): 30  
 · EMS Number: F-E, S-E  
 · Stowage Category A

## · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## · Transport/Additional information:

## · IMDG

· Limited quantities (LQ) 5L  
 · Excepted quantities (EQ) Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

## · UN "Model Regulation":

UN1993, Flammable liquids, n.o.s. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light arom., Xylenes, 2-butoxyethanol), 3, III

NA

(Contd. on page 11)

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

Trade name: **TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 10)

**15 Regulatory information**· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No REACH Annex XVII restrictions  
 Contains no REACH candidate substance

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

111-76-2	2-butoxyethanol
95-63-6	1,2,4-trimethylbenzene
1330-20-7	xylene
91-20-3	naphthalene
100-41-4	ethylbenzene
98-82-8	cumene

· **TSCA (Toxic Substances Control Act):**

64742-47-8	Distillates (petroleum), hydrotreated light
111-76-2	2-butoxyethanol
27247-96-7	2-ethylhexyl nitrate
64742-95-6	Solvent naphtha (petroleum), light arom.
64742-94-5	Solvent naphtha (petroleum), heavy arom.
95-63-6	1,2,4-trimethylbenzene
1330-20-7	xylene
108-67-8	mesitylene
178535-25-6	Benzene, ethylenated, residues, distn. lights
91-20-3	naphthalene
104-76-7	2-Ethyl-1-hexanol
100-41-4	ethylbenzene
102-25-0	1,3,5-triethylbenzene
112-80-1	oleic acid, pure
98-82-8	cumene

· **Proposition 65**· **Chemicals known to cause cancer:**

91-20-3	naphthalene
100-41-4	ethylbenzene
98-82-8	cumene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 12)

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 11)

**· Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**· Carcinogenic categories****· EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL
1330-20-7	xylene	I
91-20-3	naphthalene	C, CBD
100-41-4	ethylbenzene	D
98-82-8	cumene	D, CBD

**· TLV (Threshold Limit Value)**

111-76-2	2-butoxyethanol	A3
1330-20-7	xylene	A4
91-20-3	naphthalene	A4
100-41-4	ethylbenzene	A3

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· Canadian substance listings:****· Canadian Domestic Substances List (DSL)**

All ingredients are listed.

**· Canadian Ingredient Disclosure list (limit 0.1%)**

95-63-6	1,2,4-trimethylbenzene
108-67-8	mesitylene
100-41-4	ethylbenzene

**· Canadian Ingredient Disclosure list (limit 1%)**

111-76-2	2-butoxyethanol
----------	-----------------

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:** Engineering Department

**· Issue Date**

29.07.2015  
02/JAN/2016

**· Revision Changes:**

v 1.0 - original SDS release (29/JUL/2015)  
v 2.0 - revised flash point (02/JAN/2017)

**· Abbreviations and acronyms:**

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances

(Contd. on page 13)

NA

## Safety Data Sheet

Issue date: 07.04.2022

v 2

Last Revision Date: 29.07.2015

**Trade name: TerraDiesel Multi-function Fuel Treatment**

(Contd. of page 12)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1B: Carcinogenicity – Category 1B

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

NA