

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015




SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Product name: TerraDiesel Fuel Injector Cleaner**
 - **Part number:** 201255, 201256
 - **Application of the substance / the mixture** diesel fuel additive for cleaning
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
CPS Product Inc. - USA
1010 East 31st Street
Hialeah, FL 33013 USA
Phone: (305) 687 - 4121
cs@cpsproducts.com
 - **email of person responsible:** cs@cpsproducts.com
- **1.4 Emergency telephone number:** CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226 Flammable liquid and vapour.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Muta. 1B	H340 May cause genetic defects.
Carc. 1B	H350 May cause cancer.
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
 - **Hazard pictograms**

		
GHS02	GHS07	GHS08
 - **Signal word** Danger
 - **Hazard-determining components of labelling:**
Distillates (petroleum), hydrotreated light
Solvent naphtha (petroleum), light arom.
Solvent naphtha (petroleum), heavy arom.
Stoddard solvent
 - **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H340 May cause genetic defects.

(Contd. on page 2)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 1)

H350 May cause cancer.
 H304 May be fatal if swallowed and enters airways.
 H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P201 Obtain special instructions before use.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P321 Specific treatment (see on this label).
 P331 Do NOT induce vomiting.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P405 Store locked up.
 P501 Dispose of contents in accordance with local regulations.

· **Additional information:**

For Professional Use Only
 Restricted to professional users.

· **2.3 Other hazards**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients· **3.2 Mixtures**· **Chemical components:**

CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226; Asp. Tox. 1, H304	25-50%
CAS: 27247-96-7 EINECS: 248-363-6	2-ethylhexyl nitrate Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	10-<25%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-<25%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304; Acute Tox. 4, H332	2.5-<10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	0.1-≤2.5%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0.1-≤2.5%
CAS: 178535-25-6 EC number: 700-371-5	Benzene, ethylenated, residues, distn. lights Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1-≤2.5%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	0.1-≤2.5%

(Contd. on page 3)

GB

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 2)

CAS: 102-25-0 EINECS: 203-017-3	1,3,5-triethylbenzene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.1-≤2.5%
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304	2.5-<10%
Other Ingredients		
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304	2.5-<10%
CAS: 104-76-7 EINECS: 203-234-3	2-Ethyl-1-hexanol Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1-≤2.5%
CAS: 8052-41-3 EINECS: 232-489-3	Stoddard solvent Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304	0.1-≤2.5%
CAS: 91-20-3 EINECS: 202-049-5	naphthalene Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	<0.1%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; STOT SE 3, H335	<0.1%
CAS: 98-82-8 EINECS: 202-704-5	cumene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; STOT SE 3, H335	<0.1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures· **4.1 Description of first aid measures**· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately rinse with water. Immediately remove all contaminated clothing. If skin irritation occurs, get medical attention. Launder contaminated clothing before reuse.

· **After eye contact:**

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

· **After swallowing:**

DO NOT INDUCE VOMITING. Get immediate medical attention.

A person vomiting while laying on their back should be turned onto their side.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

May cause nose, throat, and lung irritation.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

May cause eye irritation. Symptoms may include discomfort or pain, excessive blinking and tear production, with possible redness and swelling.

(Contd. on page 4)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 3)

· **4.3 Indication of any immediate medical attention and special treatment needed**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Treat Symptomatically

SECTION 5: Firefighting measures· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water

· **5.2 Special hazards arising from the substance or mixture** See section 10 for additional information.· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

SECTION 6: Accidental release measures· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage· **7.1 Precautions for safe handling**

Open and handle receptacle with care.

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

Avoid contact with clothing.

Avoid splashes or spray in enclosed areas.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

(Contd. on page 5)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 4)

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:**

See section 10 for incompatible materials.

· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection**· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****111-76-2 2-butoxyethanol (10-<20%)**

WEL	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 123 mg/m ³ , 25 ppm Sk, BMGV
-----	---

1330-20-7 xylene (1-<2.5%)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

95-63-6 1,2,4-trimethylbenzene (1-<2.5%)

WEL	Long-term value: 125 mg/m ³ , 25 ppm ILV
-----	--

· **Ingredients with biological limit values:****111-76-2 2-butoxyethanol (10-<20%)**

BMGV	240 mmol/mol creatinine Octanol-Water: urine 0.1: post shift 7.3: butoxyacetic acid
------	--

1330-20-7 xylene (1-<2.5%)

BMGV	650 mmol/mol creatinine Octanol-Water: urine 0.1: post shift 7.3: methyl hippuric acid
------	---

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 6)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 5)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Chemical resistant protective gloves (EN 374)

· **Eye protection:**

Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

· **Body protection:** Protective work clothing**SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

- **Form:** Liquid
- **Colour:** Amber coloured
- **Odour:** Sweetish
- **Odour threshold:** Not determined.

· **pH-value:** Not determined.· **Change in condition**

- **Melting point/freezing point:** Undetermined.
- **Initial boiling point and boiling range:** Undetermined.

· **Flash point:** 43 °C· **Flammability (solid, gas):** Not applicable.· **Ignition temperature:** 210 °C· **Decomposition temperature:** Not determined.· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

- **Lower:** 0.5 Vol %
- **Upper:** 10.6 Vol %

· **Vapour pressure at 20 °C:** 2 hPa· **Density:** Not determined.

- **Relative density at 20 °C:** 0.8
- **Vapour density:** Not determined.

(Contd. on page 7)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 6)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with · water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: · Dynamic: · Kinematic:	Not determined. Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Thermal decomposition / conditions to be avoided:**
Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Heat, open flames, sparks.
- **10.5 Incompatible materials:** Strong Oxidizers
- **10.6 Hazardous decomposition products:** May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Oral	LD50	3125 mg/kg
Dermal	LD50	4280 mg/kg
Inhalative	LC50/4 h (vapor)	30.5 mg/L
27247-96-7 2-ethylhexyl nitrate		
Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	1100 mg/kg (ATE)
Inhalative	LC50/4 h (vapor)	11 mg/L (ATE)
111-76-2 2-butoxyethanol		
Oral	LD50	1414 mg/kg (gpg)
Dermal	LD50	2000 mg/kg (gpg)
Inhalative	LC50/4 h (vapor)	11.5 mg/L (gpg)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h (vapor)	>10.2 mg/L (rat)

(Contd. on page 8)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 7)

1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h (vapor)	6700 mg/L (rat)
95-63-6 1,2,4-trimethylbenzene		
Oral	LD50	5000 mg/kg (rat)
Inhalative	LC50/4 h (vapor)	18 mg/L (rat)
178535-25-6 Benzene, ethylenated, residues, distn. lights		
Oral	LD50	>2000 mg/kg (rat)
100-41-4 ethylbenzene		
Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)
Inhalative	LC50/4 h (vapor)	17.8 mg/L (rat)

- **Primary irritant effect:**
 - **Skin corrosion/irritation**
Causes skin irritation.
 - **Serious eye damage/irritation**
Causes serious eye irritation.
 - **Inhalation:** Do not inhale , can cause respiratory system irritation.
 - **Ingestion:** May be fatal if swallowed and enter airways.
- **Respiratory or skin sensitisation**
Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
 - **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity**
May cause genetic defects.
 - **Carcinogenicity**
May cause cancer.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
 - **STOT-single exposure** Based on available data, the classification criteria are not met.
 - **STOT-repeated exposure** Based on available data, the classification criteria are not met.
 - **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
 - **Aquatic toxicity:** Harmful to aquatic life with long lasting effects.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
 - **Ecotoxicological effects:**
 - **Remark:** Harmful to fish
 - **Additional ecological information:**
 - **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 9)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 8)

Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- **12.6 Other adverse effects** Avoid release to the environment.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA** UN1993

- **14.2 UN proper shipping name**

- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light arom., XYLENES, 2-butoxyethanol)

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3

- **14.4 Packing group**

- **ADR, IMDG, IATA** III

(Contd. on page 10)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 9)

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user Warning: Flammable liquids.	
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (Distillates (petroleum), hydrotreated light, 2-ethylhexyl nitrate), 3 (6.1), III

SECTION 15: Regulatory information· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

No GB REACH Annex XVII restrictions

Contains no GB REACH candidate substance

· **Directive 2012/18/EU**

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

GB

(Contd. on page 11)

Safety data sheet

Issue date: 07.04.2022

Version 2

Last Revision: 08.07.2015

Product name: TerraDiesel Fuel Injector Cleaner

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Issue Date:** 2015/07/08
- **Contact:** Engineering Department
- **Issue Date** 08.07.2015
- **Revision Changes:**
 - v 1.0 - original release (2015/07/08)
 - v 2.0 - revised (2016/08/11)
- **Abbreviations and acronyms:**
 - ADR: Agreement concerning the International Carriage of Dangerous Goods by Road
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Muta. 1B: Germ cell mutagenicity – Category 1B
 - Carc. 1B: Carcinogenicity – Category 1B
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 - Asp. Tox. 1: Aspiration hazard – Category 1
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 - Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3