1 Identification		
· Product identifier		
• Trade name: Engine Oil C	eaner	
· Part number: 206210		
<ul> <li>Details of the supplier of the sa CPS Product Inc USA 1010 East 31st Street Hialeah, FL 33013 USA Phone: (305) 687 - 4121 Email: cs@cpsproducts.com</li> <li>Manufacturer/Supplier: CPS Products Inc. 1010 East 31st Street Hialeah, Florida 33013 USA Phone: (305) 687- 4121</li> <li>email of person responsible:</li> </ul>		
• Emergency telephone numb	r <b>:</b> '03) 527-3887 (outside the US), 1-800-424-9300 (in the US) 2	94 hr

Flammable Liquids 3	H226 Flammable liquid and vapor.
Acute Toxicity - Inhalation 4	H332 Harmful if inhaled.
Germ Cell Mutagenicity 1B	H340 May cause genetic defects.
Carcinogenicity 1A	H350 May cause cancer.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.
Aquatic Acute 3	H402 Harmful to aquatic life.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

### · Label elements

\*

### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:
- Solvent naphtha (petroleum), light arom. Solvent naphtha (petroleum), heavy arom.
- 2-butoxyethanol
- Distillates (petroleum), hydrotreated heavy naphthenic
- Hazard statements Flammable liquid and vapor. Harmful if inhaled.

(Contd. on page 2)

NA

## Trade name: Engine Oil Cleaner

(Contd. of page 1)

May cause genetic defects. May cause cancer. May be fatal if swallowed and enters airways. Harmful to aquatic life. Harmful to aquatic life with long lasting effects. **Precautionary statements** Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents in accordance with local regulations. · Additional information: For Professional Use Only Restricted to professional users.

### · Other hazards

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

### **3 Composition/information on ingredients**

### · Chemical characterization: Mixtures

· Chemical components:		
64742-94-5	Solvent naphtha (petroleum), heavy arom.	25-50%
64742-95-6	Solvent naphtha (petroleum), light arom.	25-50%
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	10-25%
108-11-2	4-methylpentan-2-ol	2.5-10%
	2-butoxyethanol	2.5-10%
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	≤2.5%
71-43-2	benzene	≤2.5%
91-20-3	naphthalene	≤2.5%
98-82-8	cumene	≤2.5%
مر م الخالم ام ۸	al information. For the wording of the listed beyond phrases refer to eastion 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## **4 First-aid measures**

### • Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water. Immediately remove all contaminated clothing. If skin irritation occurs, get medical attention. Launder contaminated clothing before reuse.

(Contd. on page 3)

NA

### Trade name: Engine Oil Cleaner

(Contd. of page 2)

• After eye contact: Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- After swallowing: A person vomiting while lying on their back should be turned onto their side.
- Information for doctor: Treat Symptomatically
  - Most important symptoms and effects, both acute and delayed
  - May cause eye irritation. Symptons may include discomfort or pain, excessive blinking and tear production, with possible redness and swelling.
  - Breathing difficulty
  - Coughing

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause respiratory tract irritation.

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

- See section 11.
- Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.
   Treat Symptomatically

## **5 Fire-fighting measures**

- Extinguishing media
  - Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
  - For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture See section 10 for additional information.
- Advice for firefighters
  - Protective equipment:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. Avoid eye contact. Avoid repeated or prolonged skin contact.
- Do not touch or walk through spilled material.
- Environmental precautions:
- Inform respective authorities in case of seepage into water course or sewage system.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

NA -

### Trade name: Engine Oil Cleaner

(Contd. of page 3)

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

## 7 Handling and storage

### · Handling:

- Precautions for safe handling
- Open and handle receptacle with care.
- Avoid contact with the eyes and skin.
- Avoid contact with clothing.
- Use only in well ventilated areas.
- Avoid splashes or spray in enclosed areas.
- See section 8 for personal protective equipment.
- Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

# · Conditions for safe storage, including any incompatibilities

## Storage:

- · Requirements to be met by storerooms and receptacles:
- See section 10 for incompatible materials.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in a cool place.

Store in cool, dry, dark place, away from direct sunlight.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Control parameters

Components with limit values that require monitoring at the workplace:

108-11-2 4-m	ethylpentan-2-ol (2.5-10%)
PEL (USA)	TWA: 100 mg/m³, 25 ppm Skin
REL (USA)	STEL: 165 mg/m³, 40 ppm TWA: 100 mg/m³, 25 ppm Skin
TLV (USA)	STEL: 167 mg/m³, 40 ppm TWA: 104 mg/m³, 25 ppm Skin
EL (Canada)	STEL: 40 ppm TWA: 25 ppm Skin

(Contd. on page 5)

NA

Issue date: 04.04.2022	
------------------------	--

#### Trade name: Engine Oil Cleaner (Contd. of page 4) EV (Canada) STEL: 167 mg/m<sup>3</sup>, 40 ppm TWA: 104 mg/m<sup>3</sup>, 25 ppm Skin 111-76-2 2-butoxyethanol (2.5-10%) PEL (USA) TWA: 240 mg/m<sup>3</sup>, 50 ppm Skin REL (USA) TWA: 24 mg/m<sup>3</sup>, 5 ppm Skin TLV (USA) TWA: 97 mg/m<sup>3</sup>, 20 ppm BEI EL (Canada) TWA: 20 ppm EV (Canada) TWA: 20 ppm Skin 98-82-8 cumene (≤2.5%) PEL (USA) TWA: 245 mg/m<sup>3</sup>, 50 ppm Skin REL (USA) TWA: 245 mg/m<sup>3</sup>, 50 ppm Skin TLV (USA) TWA: (246) NIC-0.5 mg/m<sup>3</sup>, (50) NIC-0.1 ppm NIC-A3 STEL: 75 ppm EL (Canada) TWA: 25 ppm IARC 2B EV (Canada) TWA: 245 mg/m<sup>3</sup>, 50 ppm Skin 71-43-2 benzene (≤2.5%) STEL: 15\* mg/m<sup>3</sup>, 5\* ppm PEL (USA) TWA: 3\* mg/m<sup>3</sup>, 1\* ppm \*table Z-2 for exclusions in 29CFR1910.1028(d) STEL: 1 ppm REL (USA) TWA: 0.1 ppm See Pocket Guide App. A TLV (USA) STEL: 8 mg/m<sup>3</sup>, 2.5 ppm TWA: 1.6 mg/m<sup>3</sup>, 0.5 ppm

 Skin; BEI

 EL (Canada)
 STEL: 2.5 ppm

 TWA: 0.5 ppm

 Skin; ACGIH A1; IARC 1

 EV (Canada)
 STEL: 2.5 ppm

 TWA: 0.5 ppm

 Skin

 91-20-3 naphthalene (<2.5%)</td>

 PEL (USA)

 TWA: 50 mg/m³, 10 ppm

 REL (USA)

 STEL: 75 mg/m³, 15 ppm

 TWA: 50 mg/m³, 10 ppm

 (Contd. on page 6)

NA

Issue date: 04.04.2022

v 2

# Trade name: Engine Oil Cleaner

	(Contd. of page 5)
TLV (USA)	TWA: 52 mg/m³, 10 ppm Skin; BEI
EL (Canada	) TWA: 10 ppm Skin: IARC 2B
	,
EV (Canada	) STEL: 78 mg/m³, 15 ppm
	TWA: 52 mg/m³, 10 ppm
	gredients with biological limit values:
	butoxyethanol (2.5-10%)
	200 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Butoxyacetic acid with hydrolysis
	izene (≤2.5%)
	25 μg/g creatinine
	Medium: urine
	Time: end of shift Parameter Parameter: S-Phenylmercapturic acid (background
	arameter. O-r henyimercapturic acid (background
	500 μg/g creatinine
	Medium: urine
·	Time: end of shift
	Parameter: t,t-Muconic acid (background)
Addit	ional information: The lists that were valid during the creation were used as basis.
<sup>.</sup> Exposure c	ontrols
	I protective equipment:
· Gene	ral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	diately remove all soiled and contaminated clothing.
	protective clothing separately.
	hing equipment:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or r exposure use respiratory protective device that is independent of circulating air.
	ction of hands:
Tiote	ISO 374-1:2016/Type A
, m	
1112	Chemical resistant protective gloves
· Eye p	protection:
	Safety glasses. If potential for splash or mist exists, wear chemical goggles or
	faceshield.
· Body	protection: Protective work clothing
	NA

(Contd. on page 7)

Issue date: 04.04.2022

v 2

Last Revision Date: 04.04.2022

## Trade name: Engine Oil Cleaner

(Contd. of page 6)

Information on basic physical and che	emical properties
• General Information • Appearance:	
· Form:	Liquid
· Color:	Amber colored
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value at 20 °C:	7.8
Change in condition	
• Melting point/Melting range:	Undetermined.
<ul> <li>Boiling point/Boiling range:</li> </ul>	131 °C
· Flash point:	42.2 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C
<ul> <li>Decomposition temperature:</li> </ul>	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosiv air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	0.7 Vol %
· Upper:	7.5 Vol %
· Vapor pressure at 20 °C:	5 hPa
· Density at 20 °C:	0.88 g/cm <sup>3</sup>
· Relative density	Not determined.
Vapor density	Not determined.
· Evaporation rate	Not determined.
Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
· Kinematic:	Not determined.
Solvent separation test VOC content:	<42.00 %
Other information	No further relevant information available.

## **10 Stability and reactivity**

 $\cdot$  Reactivity No further relevant information available.

Issue date:	04.04.2022
-------------	------------

Last Revision Date: 04.04.2022

## Trade name: Engine Oil Cleaner

(Contd. of page 7)

· Chemical stability

Thermal decomposition / conditions to be avoided:

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid Heat, open flames, sparks.

· Incompatible materials: Strong Oxidizers, strong acids.

· Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

Acute toxicity: LD/LC50 values that are relevant for classification:		
•	te Toxicity Estim	•
Oral	LD50	16,000 mg/kg
Dermal	LD50	>4,068 mg/kg
Inhalative	LC50/4 h (vapor)	>26.1 mg/L
64742-95-	6 Solvent naphth	a (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h (vapor)	>10.2 mg/L (rat)
108-11-2 4-methylpentan-2-ol		
Oral	LD50	2,590 mg/kg (rat)
Dermal	LD50	3,560 mg/kg (rabbit)
111-76-2 2-butoxyethanol		
Oral	LD50	1,414 mg/kg (gpg)
Dermal	LD50	2,000 mg/kg (gpg)
Inhalative	LC50/4 h (vapor)	11.5 mg/L (gpg)
71-43-2 b	enzene	
Oral	LD50	4,894 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
Inhalative	LC50/4 h (vapor)	9,980 mg/L (mouse)
91-20-3 na	aphthalene	
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat)
98-82-8 ci	umene	
Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h (vapor)	24.7 mg/L (mouse)

May cause mild skin irritation. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis.

(Contd. on page 9)

NA

Trade name: Engine Oil Cleaner (Contd. of page 8) · on the eye: May cause eye irritation. · Inhalation: Do not inhale, can cause respiratory system irritation. Serious effects may be delayed after exposure. · Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting. May be fatal if swallowed and enter airways. · Sensitization: No sensitizing effects known. · Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Carcinogenic. The product can cause inheritable damage. · IARC (International Agency for Research on Cancer) 111-76-2 2-butoxyethanol 3 98-82-8 cumene 2B 71-43-2 benzene 1 91-20-3 naphthalene 2B · NTP (National Toxicology Program) 98-82-8 cumene R 71-43-2 benzene Κ 91-20-3 naphthalene R **OSHA-Ca** (Occupational Safety & Health Administration) 71-43-2 benzene

## **12 Ecological information**

· Toxicity

Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

### · Behavior in environmental systems:

### Bioaccumulative potential

108-11-2 4-methylpentan-2-ol

Bioaccumulation 1.43 (-) (potential low)

· Mobility in soil No further relevant information available.

### · Ecotoxical effects:

Remark: Harmful to fish

### · Additional ecological information:

### General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

## Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

(Contd. on page 10)

Issue date: 04.04.2022

v 2

Last Revision Date: 04.04.2022

Trade name: Engine Oil Cleaner

(Contd. of page 9)

· Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1993
UN proper shipping name DOT	Flammable liquids, n.o.s. (Solvent naphth (petroleum), light arom., Benzene, Methyl isobut carbinol)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Solvent naphtr (petroleum), light arom., BENZENE, METHY ISOBUTYL CARBINOL)
Transport hazard class(es)	
DOT	
PLAMMBLE LOUD	
· Class · Label	3 Flammable liquids 3
· IMDG, IATA	
Class	3 Flammable liquids
· Label	3
<ul> <li>Packing group</li> <li>DOT, IMDG, IATA</li> </ul>	Ш
Environmental hazards: Marine pollutant:	Νο
• Special precautions for user • Hazard identification number (K	Warning: Flammable liquids <b>(emler code):</b> 30
、	(Contd. on page

v 2	Last Revision Date: 04.04.2022
	(Contd. of page 10)
F-E, <u>S-E</u> A	
Not applicable.	
5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
· UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (SC NAPHTHA (PETROLEUM), LIGHT A BENZENE, METHYL ISOBUTYL CARBINOL),	
	F-E, <u>S-E</u> A Not applicable. 5L Code: E1 Maximum net mI Maximum ne 1000 ml UN 1993 FLAMMAI NAPHTHA (PET

## **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No REACH Annex XVII restrictions Contains no REACH candidate substance

### · Sara

• ;	Section 355 (extremely hazardous substances):			
None of th	ne ingredients is listed.			
- :	Section 313 (Specific toxic chemical listings):			
111-76-2	-butoxyethanol			
98-82-8	umene			
71-43-2	benzene			
91-20-3	aphthalene			
·TS	CA (Toxic Substances Control Act):			
64742-94-	5 Solvent naphtha (petroleum), heavy arom.			
64742-95-	6 Solvent naphtha (petroleum), light arom.			
64742-52-	-5 Distillates (petroleum), hydrotreated heavy naphthenic			
108-11-	-2 4-methylpentan-2-ol			
111-76-	2 2-butoxyethanol			
68649-42-	-3 Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts			
98-82-	-8 cumene			
71-43-	-2 benzene			
91-20-	-3 naphthalene			
	(Contd. on page 12)			

Issue	date:	04.04	.2022
-------	-------	-------	-------

## Trade name: Engine Oil Cleaner (Contd. of page 11) Proposition 65 · Chemicals known to cause cancer: 98-82-8 cumene 71-43-2 benzene 91-20-3 naphthalene · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: 71-43-2 benzene · Chemicals known to cause developmental toxicity: 71-43-2 benzene Carcinogenic categories · EPA (Environmental Protection Agency) 111-76-2 2-butoxyethanol NL 98-82-8 cumene D, CBD 71-43-2 benzene A, K/L 91-20-3 naphthalene C, CBD · TLV (Threshold Limit Value) 111-76-2 2-butoxyethanol A3 71-43-2 benzene A1 91-20-3 naphthalene A4 · NIOSH-Ca (National Institute for Occupational Safety and Health) 71-43-2 benzene · Canadian substance listings: · Canadian Domestic Substances List (DSL) All ingredients are listed. Canadian Ingredient Disclosure list (limit 0.1%) 71-43-2 benzene Canadian Ingredient Disclosure list (limit 1%) 108-11-2 4-methylpentan-2-ol 111-76-2 2-butoxyethanol 98-82-8 cumene 91-20-3 naphthalene

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact: Engineering Department

· Issue Date 04.04.2022

Last Revision Date: 04.04.2022

### Trade name: Engine Oil Cleaner (Contd. of page 12) · Abbreviations and acronyms: ADR: Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Inhalation 4: Acute toxicity – Category 4 Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B Carcinogenicity 1A: Carcinogenicity - Category 1A Aspiration Hazard 1: Aspiration hazard - Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \*\* Data compared to the previous version altered.