Issue date: 21.04.2022 Version 3 Last Revision: 15.01.2015

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### · 1.1 Product identifier

Product name: Terraclean Extended Interval Engine Oil Cleaner

Part number: 206230

· Application of the substance / the mixture Engine Oil cleaner

#### · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: CPS Product Inc. - USA 1010 East 31st Street Hialeah, FL 33013 USA Phone: (305) 687 - 4121 cs@cpsproducts.com

email of person responsible: cs@cpsproducts.com

1.4 Emergency telephone number: CHEMTREC International +1 (703) 527-3887 24 hr

## **SECTION 2: Hazards identification**

#### · 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

(R)-p-mentha-1,8-diene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

(Contd. on page 2)

## Product name: Terraclean Extended Interval Engine Oil Cleaner

(Contd. of page 1)

P264 Wash thoroughly after handling.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents in accordance with local regulations.

#### · 2.3 Other hazards

· **PBT:** Not applicable. · **vPvB:** Not applicable.

# **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

	· Chemical components:		
	CAS: 111-76-2	2-butoxyethanol	25-50%
	EINECS: 203-905-0	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
		(R)-p-mentha-1,8-diene	25-50%
		Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

#### · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

## · After skin contact:

Wash with plenty of soap and water. Remove contaminated clothing. If skin irritation occurs, get medical attention. Launder contaminated clothing before reuse.

## · After eye contact:

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- · After swallowing: DO NOT INDUCE VOMITING. Get immediate medical attention.
- · Information for doctor: Treat Symptomatically

## 4.2 Most important symptoms and effects, both acute and delayed

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause respiratory tract irritation.

(Contd. on page 3)

Issue date: 21.04.2022 Version 3 Last Revision: 15.01.2015

## Product name: Terraclean Extended Interval Engine Oil Cleaner

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
  - · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
  - For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture See section 10 for additional information.
- · 5.3 Advice for firefighters
  - Protective equipment:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

## **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat.

- · 7.2 Conditions for safe storage, including any incompatibilities
  - · Storage:
    - · Requirements to be met by storerooms and receptacles:

See section 10 for incompatible materials.

· Information about storage in one common storage facility: Not required.

(Contd. on page 4)

Issue date: 21.04.2022 Version 3 Last Revision: 15.01.2015

## Product name: Terraclean Extended Interval Engine Oil Cleaner

(Contd. of page 3)

#### · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

#### 111-76-2 2-butoxyethanol (25-50%)

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm

Sk, BMGV

## Ingredients with biological limit values:

## 111-76-2 2-butoxyethanol (25-50%)

BMGV 240 mmol/mol creatinine

Octanol-Water: urine

0.1: post shift

7.3: butoxyacetic acid

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

## · Personal protective equipment:

## · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:

Nitrile. Neoprene.

Long sleeve shirt is recommended. Launder contaminated clothing before reuse.





Chemical resistant protective gloves (EN 374)

#### · Eye protection:



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

GB

Issue date: 21.04.2022 Version 3 Last Revision: 15.01.2015

# **Product name: Terraclean Extended Interval Engine Oil Cleaner**

(Contd. of page 4)

9.1 Information on basic physical and chemical properties General Information Appearance: Form: Colour: Amber coloured Citrus Odour threshold: Not determined.  PH-value at 20 °C: Initial boiling point and boiling range: Initial boiling range: Initial boiling range: Intital boiling range: Int	SECTION 9: Physical and chem	SECTION 9: Physical and chemical properties			
Appearance:     Form:     Colour:     Codour:     Odour threshold:     Not determined.  PH-value at 20 °C:  Change in condition     Melting point/freezing point:     Initial boiling point and boiling range: 171 °C  Flash point:     Sa °C  Flammability (solid, gas):     Not applicable.  Ignition temperature:     Decomposition temperature:     Not determined.  Auto-ignition temperature:     Product is not selfigniting.  Explosive properties:     Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:     Lower:	9.1 Information on basic physical and	I chemical properties			
Form: Colour: Odour: Odour: Odour threshold: Not determined.  PH-value at 20 °C: Change in condition Melting point/freezing point: Initial boiling point and boiling range: 171 °C  Flash point: Ignition temperature: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: Undetermined. Not determined.  Product is not selfigniting.  Explosion limits: Lower: Upper: Upper: Upper: Upper: Upper: Upper: Upper: Not determined. Not determined.  Solubility in / Miscibility with water: Not determined. Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) Not determined.	General Information				
Colour: Odour: Odour threshold: Not determined.  PH-value at 20 °C: Change in condition Melting point/freezing point: Undetermined. Undetermined. Initial boiling point and boiling range: 171 °C Flash point: S3 °C Flammability (solid, gas): Not applicable. Ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: Upper: 10.6 Vol % Vapour pressure at 20 °C: Relative density Vapour density Vapour density Not determined. Solubility in / Miscibility with water: Not determined.  Solubility in / Miscibility with water: Not determined. Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s Solvent separation test: VOC (EC)  Solvent separation test: VOC (EC)  Audetermined. Citrus Not determined.	• •	1 invital			
Odour threshold: Odour threshold: Not determined.  pH-value at 20 °C: Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 171 °C Flash point: Flash point: S3 °C Flammability (solid, gas): Not applicable. Ignition temperature: Polecomposition temperature: Not determined.  Auto-ignition temperature: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: 0,7 Vol % Upper: 0,6 Vol % Vapour pressure at 20 °C: Relative density Vapour density Vapour density Evaporation rate Solubility in / Miscibility with water: Not determined. Solubility in / Miscibility with water: Not determined. Not determined. Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s Solvent separation test: VOC (EC)  60.0 %					
Odour threshold:  PH-value at 20 °C:  Change in condition Melting point/freezing point: Initial boiling point and boiling range: 171 °C  Flash point:  Flash point:  Ignition temperature:  Decomposition temperature:  Auto-ignition temperature:  Explosive properties:  Explosion limits: Lower: Upper:  Upper:  Density at 20 °C:  Relative density Vapour density Vapour density Evaporation rate  Solubility in / Miscibility with water:  Partition coefficient: n-octanol/water:  Not determined.					
pH-value at 20 °C:  Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 171 °C  Flash point: Flash point: Flammability (solid, gas): Not applicable. Ignition temperature: Product is not selfigniting.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: Upper: 10.6 Vol % Vapour pressure at 20 °C: Relative density Vapour density Vapour density Vapour density Vapour density Not determined. Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC)  Not determined.  Not determined.  Not determined.  Not determined.  Not determined.		•			
Melting point/freezing point: Initial boiling point and boiling range: 171 °C  Flash point: 53 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 240 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Product is not selfigniting.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: 0.7 Vol %  Upper: 10.6 Vol %  Vapour pressure at 20 °C: 2.3 hPa  Density at 20 °C: 0.875 g/cm³ Relative density Not determined. Yapour density Not determined. Not determined. Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Not determined. Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %					
Melting point/freezing point: Initial boiling point and boiling range: 171 °C  Flash point:  Flammability (solid, gas): Not applicable.  Ignition temperature:  Decomposition temperature:  Auto-ignition temperature: Product is not selfigniting.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: 10.6 Vol %  Vapour pressure at 20 °C: Relative density Vapour density Vapour density Evaporation rate  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC)  Not determined.  1.77 mm²/s	· Change in condition				
Flammability (solid, gas):  Ignition temperature:  Decomposition temperature:  Auto-ignition temperature:  Froduct is not selfigniting.  Explosive properties:  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper:  10.6 Vol %  Vapour pressure at 20 °C: Relative density Vapour density Vapour density Evaporation rate  Not determined.  Solubility in / Miscibility with water:  Not miscible or difficult to mix.  Partition coefficient: n-octanol/water:  Not determined.  Viscosity: Dynamic: Kinematic at 40 °C: Not determined.  1.77 mm²/s  Solvent separation test: VOC (EC)  60.0 %	· Melting point/freezing point:	Melting point/freezing point: Undetermined.			
Ignition temperature: 240 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Product is not selfigniting.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: 0.7 Vol % Upper: 10.6 Vol %  Vapour pressure at 20 °C: 2.3 hPa  Density at 20 °C: 0.875 g/cm³ Relative density Not determined. Vapour density Not determined. Solubility in / Miscibility with water: Not determined.  Solubility in / Miscibility with water: Not determined.  Viscosity: Dynamic: Not determined.  Viscosity: Dynamic: Not determined.  Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %	· Flash point:	53 °C			
Decomposition temperature:  Not determined.  Auto-ignition temperature:  Product is not selfigniting.  Explosive properties:  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower:  Done of the product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower:  Done of the product is not selfigniting.  Outpoor of the product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Done of the product is not selfigniting.  Outpoor of the product is not seplosive. However, formation of explosive air/vapour mixtures are possible.  Outpoor of the product is not sexplosive. However, formation of explosive air/vapour mixtures are possible.  Outpoor of the product is not sexplosive. However, formation of explosive air/vapour mixtures are possible.  Outpoor of the product is not sexplosive. However, formation of explosive air/vapour mixtures are possible.  Outpoor of the product is not sexplosive. However, formation of explosive.  Outpoor of the product is not sexplosive. However, formation of explosive.  Outpoor of the product is not sexplosive.  Outpoor of the product is not s	· Flammability (solid, gas):	Not applicable.			
Auto-ignition temperature:  Product is not selfigniting.  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: Upper: 10.6 Vol %  Vapour pressure at 20 °C: Relative density Vapour density Vapour density Evaporation rate Not determined. Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC)  Not determined. 60.0 %	· Ignition temperature:	240 °C			
Explosive properties:  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: Upper: 10.6 Vol %  Vapour pressure at 20 °C: Relative density Vapour density Vapour density Vapour density Not determined. Vapour density Not determined.  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %	· Decomposition temperature:	Not determined.			
air/vapour mixtures are possible.  Explosion limits:     Lower: 0.7 Vol %     Upper: 10.6 Vol %  Vapour pressure at 20 °C: 2.3 hPa  Density at 20 °C: 0.875 g/cm³     Relative density Not determined.     Vapour density Not determined.     Evaporation rate Not determined.  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity:     Dynamic: Not determined.     Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test:     VOC (EC) 60.0 %	· Auto-ignition temperature:	Product is not selfigniting.			
Lower: Upper: 10.6 Vol %  Vapour pressure at 20 °C: 2.3 hPa  Density at 20 °C: Relative density Vapour density Vapour density Evaporation rate  Not determined.  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %	· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.			
Upper: 10.6 Vol %  Vapour pressure at 20 °C: 2.3 hPa  Density at 20 °C: 0.875 g/cm³ Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined.  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Not determined. Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %					
Vapour pressure at 20 °C:  Density at 20 °C:  Relative density  Vapour density  Vapour density  Vapour density  Not determined.  Vaporation rate  Not determined.  Solubility in / Miscibility with  water:  Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity:  Dynamic:  Not determined.  Kinematic at 40 °C:  1.77 mm²/s  Solvent separation test:  VOC (EC)  60.0 %					
Density at 20 °C: Relative density Vapour density Evaporation rate  Not determined. Not determined. Not determined.  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Not determined.  Not determined.  Not determined.  1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %	· Upper:	10.6 Vol %			
Relative density Vapour density Not determined. Evaporation rate  Not determined.  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Not determined.  Not determined.  Not determined.  Not determined.  Solvent separation test: VOC (EC) 60.0 %	· Vapour pressure at 20 °C:	2.3 hPa			
Vapour density Evaporation rate  Not determined.  Not determined.  Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Not determined. Kinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %					
<ul> <li>Evaporation rate Not determined.</li> <li>Solubility in / Miscibility with <ul> <li>water: Not miscible or difficult to mix.</li> </ul> </li> <li>Partition coefficient: n-octanol/water: Not determined.</li> <li>Viscosity: <ul> <li>Dynamic: Not determined.</li> <li>Kinematic at 40 °C: 1.77 mm²/s</li> </ul> </li> <li>Solvent separation test: <ul> <li>VOC (EC)</li> <li>60.0 %</li> </ul> </li> </ul>					
Solubility in / Miscibility with water: Not miscible or difficult to mix.  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Not determined. Tinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %					
<ul> <li>water: Not miscible or difficult to mix.</li> <li>Partition coefficient: n-octanol/water: Not determined.</li> <li>Viscosity: <ul> <li>Dynamic: Not determined.</li> <li>Kinematic at 40 °C: 1.77 mm²/s</li> </ul> </li> <li>Solvent separation test: <ul> <li>VOC (EC)</li> <li>60.0 %</li> </ul> </li> </ul>	· Evaporation rate	Not determined.			
Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic: Not determined. Tinematic at 40 °C: 1.77 mm²/s  Solvent separation test: VOC (EC) 60.0 %					
· Viscosity:  · Dynamic:  · Kinematic at 40 °C:  · Solvent separation test:  · VOC (EC)  Not determined.  1.77 mm²/s  60.0 %					
<ul> <li>Dynamic: Not determined.</li> <li>Kinematic at 40 °C: 1.77 mm²/s</li> <li>Solvent separation test:</li> <li>VOC (EC) 60.0 %</li> </ul>	· Partition coefficient: n-octanol/water: Not determined.				
· Kinematic at 40 °C: 1.77 mm²/s  · Solvent separation test: · VOC (EC) 60.0 %					
· Solvent separation test: · VOC (EC) 60.0 %					
VOC (EC) 60.0 %	· Kinematic at 40 °C:	1./7 mm²/s			
• 9.2 Other information No further relevant information available.		60.0 %			
	· 9.2 Other information	No further relevant information available.			

# **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

Issue date: 21.04.2022 Version 3 Last Revision: 15.01.2015

## Product name: Terraclean Extended Interval Engine Oil Cleaner

(Contd. of page 5)

#### · 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Heat, open flames, sparks.
- · 10.5 Incompatible materials: Strong Oxidizers
- 10.6 Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

# **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
  - · Acute toxicity Based on available data, the classification criteria are not met.

	· LD/	· LD/LC50 values relevant for classification:		
Ī	ATE (Acute Toxicity Estimates)			
Ī	Oral	LD50	1567 mg/kg (rat)	
	Dermal	LD50	1333 mg/kg (rab)	
	Inhalative	LC50/4 h (vapor)	13 mg/L (rat)	
111-76-2		2-butoxyethanol		
Ī	Oral	LD50	470 mg/kg (rat)	
	Dermal	LD50	400 mg/kg (rab)	
	Inhalative	LC50/4 h (vapor)	3.9 mg/L (rat)	
	5989-27-5	27-5 (R)-p-mentha-1,8-diene		
	Oral	LD50	4400 mg/kg (rat)	
	Dermal	LD50	>5 g/Kg (rabbit)	

- · Primary irritant effect:
  - · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Ingestion:

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

Respiratory or skin sensitisation

May produce an allergic reaction.

May cause an allergic skin reaction.

- · Additional toxicological information:
  - · Acute effects (acute toxicity, irritation and corrosivity)

Harmful if swallowed. Harmful in contact with skin. Toxic if inhaled.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
  - · Germ cell mutagenicity Based on available data, the classification criteria are not met.
  - · Carcinogenicity Based on available data, the classification criteria are not met.
  - Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)

Issue date: 21.04.2022 Version 3 Last Revision: 15.01.2015

## Product name: Terraclean Extended Interval Engine Oil Cleaner

(Contd. of page 6)

· Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

#### · 12.1 Toxicity

· Aquatic toxicity:			
111-76-2 2-butoxyethanol			
EC50 (48 h)	>1000 mg/L (daphnia)		
LC50 (96 h) (static) 1490 mg/L (Lepomis macrochirus)			
5989-27-5 (R)-p-mentha-1,8-diene			
LC50 (96 h)	0.619-0.796 mg/L (Pimephales promelas)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
  - · Ecotoxical effects:
    - Remark: Very toxic for fish
  - · Additional ecological information:
    - · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
  - · **PBT:** Not applicable.
  - · vPvB: Not applicable.
- · 12.6 Other adverse effects Avoid release to the environment.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
  - Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
  - · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number	LINUAGO
· ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name	
· ADR	UN1993 FLAMMABLE LIQUID, N.O.S (DIPENTENE, 2-butoxyethanol)
	(Contd. on page

(Contd. on page 8)

## Product name: Terraclean Extended Interval Engine Oil Cleaner

(Contd. of page 7) · IMDG FLAMMABLE LIQUID, N.O.S. (DIPENTENE, 2butoxyethanol), MARINE POLLUTANT · IATA FLAMMABLE LIQUID, N.O.S. (DIPENTENE, 2butoxyethanol) · 14.3 Transport hazard class(es) · ADR 3 (F1) Flammable liquids. · Class · Label · IMDG, IATA 3 Flammable liquids. · Class · Label · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: Product contains environmentally hazardous substances: (R)-p-mentha-1,8-diene · Marine pollutant: Yes · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 30 · EMS Number: F-E.S-E Stowage Category Α · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 51 · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml

Issue date: 21.04.2022 Version 3 Last Revision: 15.01.2015

## Product name: Terraclean Extended Interval Engine Oil Cleaner

(Contd. of page 8)

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (DIPENTENE, 2-BUTOXYETHANOL), 3, III

# **SECTION 15: Regulatory information**

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No GB REACH Annex XVII restrictions
Contains no GB REACH candidate substance

- Directive 2012/18/EU
  - · Named dangerous substances ANNEX I None of the ingredients is listed.
  - · Seveso category

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Issue Date: 2016/02/17
- · Contact: Engineering Department
- · Issue Date 15.01.2015
- · Revision Changes:

v 1.0 - initial SDS release (2016/02/17)

v 2.0 - revised (2016/07/26)

## Abbreviations and acronyms:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1