

## 1. Subject and range of tests:

Testing furniture for compliance with standards

## 2. Order number: RDM 42/A/17/S

## 3. Customer's name and address:

**Noti Sp. z o.o.**  
**Ul. Sowia 19**  
**62-080 Tarnowo Podgórne**

## 4. Name and symbol of the tested furniture:

**Chair Mishell**  
**Armchair Mishell**

## 5. Date of tests: 15.09.2017 - 29.09.2017

## 6. Identification of furniture covered by the tests:

The technical description and product design drawing

## 7. The list of standards according to which tests were conducted:

PN-EN 1728:2012  
PN-EN 16139:2013\_07  
PN-EN 1022:2007

## 8. Test results:

The results of strength, durability and stability tests together with the evaluation of test results are given in the following cards 1-36/17/S to 3-36/17 / S of the report from tests No. 36/17/S.

The test results presented in the report relate to the examined samples exclusively. The report card from tests can not be duplicated fragmentary or in the whole.

## 9. Evaluation of test results:

The above mentioned products are consistent with the requirements of the standards.

Head of Furniture Testing Laboratory

Head of Department of Furniture Design

M.Sc. eng. Karol Labęda

UNIwersytet PRzyrodniczy  
w Poznaniu  
WYDZIAŁ TECHNOLOGII DREWNA  
KATEDRA MEBLARSTWA  
LABORATORIUM BADANIA MEBLI  
ul. Wojska Polskiego 38/42  
60-627 POZNAN  
tel. 61-848-74-75, 61-848-74-79

Prof. dr. eng. Jerzy Smardzewski

Poznań, 29.09.2017

Card no. 1 - 36/17/S

## Strength and durability tests. **PIECE OF FURNITURE FOR SEATING**

The name and type of furniture: Chair Mishell  
Mass of furniture in N: 75  
Furniture dimensions in mm: height: 820 width: 520 depth: 560

**Methodology: PN-EN 1728:2012**

**Requirements: PN-EN 16139:2013\_07 - level 2**

The standard point	Test	Test specifications/parameters	Test results
6.4	Seat static load and back static load test	Seat: force 2000 N Back: force 700 N 10 times	Positive
6.5	Seat front edge static load test	Seat: force 1600 N 10 times	Positive
6.6	Vertical load on back rests	The vertical force 900 N 10 times	Positive
6.7	Horizontal forward static load test on back rests	The horizontal force 450 N 10 times	Positive
6.10	Arm rest sideways static load test	The horizontal force 900 N 10 times	Positive
6.11	Arm rest downwards static load test	The vertical force 900 N 10 times	Positive
6.15	Leg forward static load test	Seat: force 1800 N The horizontal force 620 N 10 times	Positive
6.16	Leg sideways static load test	Seat: force 1800 N The horizontal force 620 N 10 times	Positive

Research executed: M. Sc. eng. Karol Łabęda .....

Results checked: M. Sc. eng. Rafał Westerski .....

Card no. 2 - 36/17/S

## Strength and durability tests. **PIECE OF FURNITURE FOR SEATING**

The name and type of furniture: Chair Mishell

**Methodology: PN-EN 1728:2012**

**Requirements: PN-EN 16139:2013\_07 - level 2**

The standard point	Test	Test specifications/parameters	Test results
6.17	Combined seat and back durability test	Seat: force 1000 N Back: force 300 N 200.000 times	Positive
6.18	Seat front edge durability test	Seat: force 1000 N 100.000 times	Positive
6.20	Arm rest durability test	The vertical force 400 N 60.000 times	Positive
6.24	Seat impact test	Drop height 300 mm 10 times	Positive
6.25	Back impact test	Drop height 330 mm 10 times	Positive
6.26	Arm impact test	Drop height 330 mm 10 times	Positive

Research executed: M. Sc. eng. Karol Łabęda .....

Results checked: M. Sc. eng. Rafał Westerski .....



Card no. 3 - 36/17/S

Stability test. **PIECE OF FURNITURE FOR SEATING**

The name and type of furniture: Chair Mishell  
Height of the seat  $h_s$  in mm: 460

**Methodology and requirements: PN-EN 1022:2007**

The standard point	Test	Test specifications/parameters	Test results
6.2	Forward stability	The vertical force 600 N The horizontal force 20 N 5 s	Positive
6.5	Sideways stability of chairs with armrests	The vertical force 250 N + 350 N The horizontal force 20 N 5 s	Positive
6.6*	Rearwards stability	The vertical force 600 N The horizontal force 160 N 5 s	Positive

\*(6.6) The horizontal force:  $F = (1000 - h_s) * 0,2857$  [N]

Research executed: M. Sc. eng. Karol Łabęda

Results checked: M. Sc. eng. Rafał Westerski

