

ProQ Aluminium loose flange

Dimension table

			Drilling PN 10			ProQ PN 10 (DIN 2462 dimensions) EN AC-47000 (AISI12Cu)		
	DN	D	dk	d ₂	st	ISO d ₆	NS d ₆	b
PN 10/16	10	90	60	14	4	19	19	16
	15	95	65	14	4	24	23	16
	20	105	75	14	4	30	28	16
	25	115	85	14	4	36	33	16
	32	140	100	18	4	46	42	16
	40	150	110	18	4	54	48	18
	50	165	125	18	4	65	60	18
	65	185	145	18	4	81	75	18
	80	200	160	18	8	94	90	20
	100	220	180	18	8	119	111	20
PN 10 (mating dimensions)	125	250	210	18	8	145	136	22
	150	285	240	22	8	173	161	22
	200	340	295	22	8	225	212	24
	250	395	350	22	12	279	264	26
	300	445	400	22	12	329	315	26
	350	505	460	22	16	362	362	26
	400	565	515	26	16	413	413	32
	450	615	565	26	20	465	465	32
	500	670	620	26	20	517	517	34
	600	780	725	30	20	618	618	36
	700	895	840	30	24	721	721	40
	800	1015	950	33	24	824	824	44
900	1115	1050	33	28	920	920	44	
1000	1230	1160	36	28	1020	1020	44	
1100	1340	1270	36	32		1124	44	
1200	1455	1380	39	32	1232	1232	52	

