


## Geberit PE -haarayhde 88,5°



Esimerkkikuva



### Käyttötarkoitukset

- Kiinteistöviemärijärjestelmiin
- Tonttiviemärintiin

### Ominaisuuudet

- UV-kestävä

### Tekniset tiedot

Materiaali

PE-HD

Tuotenro	LVI nro.	DN	d, Ø	d1, Ø	arc	H	X1	X2	X3	K1	K2	K3
379.158.16.1	2300904	30 / 30	32 mm	32 mm	88.5 °	8.5 cm	5 cm	3.5 cm	3.5 cm	2.5 cm	1 cm	1 cm
360.159.16.1	2300850	40 / 40	40 mm	40 mm	88.5 °	13 cm	7.5 cm	5.5 cm	5.5 cm	4.5 cm	2.5 cm	2.5 cm
360.158.16.1	2300849	40 / 30	40 mm	32 mm	88.5 °	13 cm	7.5 cm	5.5 cm	5.5 cm	5 cm	2.5 cm	2 cm
361.159.16.1	2300851	50 / 40	50 mm	40 mm	88.5 °	15 cm	9 cm	6 cm	6 cm	6 cm	2.5 cm	3 cm
361.162.16.1	2300852	50 / 50	50 mm	50 mm	88.5 °	15 cm	9 cm	6 cm	6 cm	5.5 cm	2.5 cm	2.5 cm
363.162.16.1	2300853	56 / 50	56 mm	50 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	3 cm	3.5 cm
363.165.16.1	2300854	56 / 56	56 mm	56 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6.5 cm	3 cm	3 cm
364.159.16.1	2300855	60 / 40	63 mm	40 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	3 cm	3 cm
364.162.16.1	2300856	60 / 50	63 mm	50 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	3 cm	3.5 cm
364.165.16.1	2300857	60 / 56	63 mm	56 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6.5 cm	3 cm	3 cm
364.170.16.1	2300858	60 / 60	63 mm	63 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6 cm	3 cm	3 cm
365.159.16.1	2300859	70 / 40	75 mm	40 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7.5 cm	2.5 cm	4 cm
365.162.16.1	2300860	70 / 50	75 mm	50 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	2.5 cm	3.5 cm
365.165.16.1	2300861	70 / 56	75 mm	56 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6.5 cm	2.5 cm	3 cm
365.170.16.1	2300862	70 / 60	75 mm	63 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6 cm	2.5 cm	2.5 cm
365.175.16.1	2300863	70 / 70	75 mm	75 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	5.5 cm	2.5 cm	2.5 cm
366.159.16.1	2300864	90 / 40	90 mm	40 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	8.5 cm	2.5 cm	4.5 cm
366.162.16.1	2300865	90 / 50	90 mm	50 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	8.5 cm	2.5 cm	4.5 cm
366.165.16.1	2300866	90 / 56	90 mm	56 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	8 cm	2.5 cm	4 cm
366.170.16.1	2300867	90 / 60	90 mm	63 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	7.5 cm	2.5 cm	3.5 cm
366.175.16.1	2300868	90 / 70	90 mm	75 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	7 cm	2.5 cm	3 cm
366.180.16.1	2300869	90 / 90	90 mm	90 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	6.5 cm	2.5 cm	2.5 cm
367.159.16.1	2300870	100 / 40	110 mm	40 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	10 cm	2.5 cm	6 cm
367.162.16.1	2300871	100 / 50	110 mm	50 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	9.5 cm	2.5 cm	5 cm
367.165.16.1	2300872	100 / 56	110 mm	56 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	9 cm	2.5 cm	4.5 cm
367.170.16.1	2300873	100 / 60	110 mm	63 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	9 cm	2.5 cm	4 cm
367.175.16.1	2300874	100 / 70	110 mm	75 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	8.5 cm	2.5 cm	3.5 cm
367.180.16.1	2300875	100 / 90	110 mm	90 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	7.5 cm	2.5 cm	3 cm
367.185.16.1	2300876	100 / 100	110 mm	110 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	6.5 cm	2 cm	2 cm
368.162.16.1	2300877	125 / 50	125 mm	50 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	11 cm	2.5 cm	6 cm
368.165.16.1	2300878	125 / 56	125 mm	56 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	10.5 cm	2.5 cm	5.5 cm

Tuotenro	LVI nro.	DN	d, ø	d1, ø	arc	H	X1	X2	X3	K1	K2	K3
368.170.16.1	2300879	125 / 60	125 mm	63 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	10.5 cm	2.5 cm	5 cm
368.175.16.1	2300880	125 / 70	125 mm	75 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	10 cm	2.5 cm	4.5 cm
368.180.16.1	2300881	125 / 90	125 mm	90 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	9 cm	2.5 cm	4 cm
368.185.16.1	2300882	125 / 100	125 mm	110 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	8 cm	2 cm	3 cm
368.189.16.1	2300883	125 / 125	125 mm	125 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	7 cm	2 cm	2 cm
369.175.16.1	2300884	150 / 70	160 mm	75 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	15 cm	4.5 cm	8 cm
369.185.16.1	2300885	150 / 100	160 mm	110 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	13.5 cm	4.5 cm	6 cm
369.189.16.1	2300886	150 / 125	160 mm	125 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	12.5 cm	4.5 cm	5 cm
369.195.16.1	2300887	150 / 150	160 mm	160 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	10.5 cm	3.5 cm	3 cm
370.180.16.1	2300888	200 / 90	200 mm	90 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	3 cm	0 cm
370.185.16.1	2300889	200 / 100	200 mm	110 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	3 cm	0 cm
370.189.16.1	2300890	200 / 125	200 mm	125 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	3 cm	0 cm
370.195.16.1	2300891	200 / 150	200 mm	160 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	2 cm	0 cm
370.196.16.1	2300892	200 / 200	200 mm	200 mm	88.5 °	40 cm	20 cm	20 cm	20 cm	0 cm	0 cm	0 cm
371.185.16.1	2300893	250 / 100	250 mm	110 mm	88.5 °	44 cm	22 cm	22 cm	22 cm	3.5 cm	4 cm	3.5 cm
371.189.16.1	2300894	250 / 125	250 mm	125 mm	88.5 °	44 cm	22 cm	22 cm	22 cm	3 cm	4 cm	3 cm
371.195.16.1	2300895	250 / 150	250 mm	160 mm	88.5 °	44 cm	22 cm	22 cm	22 cm	0 cm	3.5 cm	0 cm
371.196.16.1	2300896	250 / 200	250 mm	200 mm	88.5 °	48 cm	24 cm	24 cm	24 cm	0 cm	0 cm	0 cm
371.197.16.1	2300897	250 / 250	250 mm	250 mm	88.5 °	48 cm	24 cm	24 cm	24 cm	0 cm	0 cm	0 cm
372.185.16.1	2300898	300 / 100	315 mm	110 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	9.5 cm	6 cm	9.5 cm
372.189.16.1	2300899	300 / 125	315 mm	125 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	9 cm	6 cm	9 cm
372.195.16.1	2300900	300 / 150	315 mm	160 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	7 cm	6 cm	7 cm
372.196.16.1	2300901	300 / 200	315 mm	200 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	4.5 cm	0 cm	4.5 cm
372.197.16.1	2300902	300 / 250	315 mm	250 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	2 cm	0 cm	2 cm
372.198.16.1	2300903	300 / 300	315 mm	315 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	0 cm	0 cm	0 cm