

Conex Compression

A range of Compression fittings.



Features and Benefits:

- Conex Compression fittings are compatible with EN1057 equivalent copper tube to EN1057.
- Conex Compression fittings are suitable for connecting polybutylene pipes (PB) and PEX to EN15876-2, EN15875-2 and BS57291:2 and 3.
- Fittings compatible with PB and PEX pipes are available in dimensions 10,15,18,22 and 28mm.
- Used in plumbing, heating, cooling, compressed air and gas applications.
- They are manufactured in duplex brass. Many items are also available in dezincification resistance (DZR) brass.
- Manufactures in accordance with EN 1252-2 and threaded connection to EN1254-4.
- Suitable for Flame Free installations.
- PTFE tape is not required for installation.
- Installation with PB and PEX pipe requires liners recommended by the tube manufacturer or supplied by IBP.
- Imperial tube sizes can be connected with special rings and adapters.



Conex Compression

A range of Conex Compression fittings

Straight Coupler  301 (\$301) From: 6mm To: 108mm	Reduced Straight Coupler  301 RED (\$301 RED) From: 8 x 6mm To: 35 x 28mm	Straight Coupler Bulkhead  301BH From: 15mm To: 15mm	Cross Over  301CO From: 15mm To: 22mm	Straight Coupler with Drain Tap  301DA From: 15mm To: 22mm	Imperial to Metric Straight Coupler  301IM From: 76 x 3" To: 76 x 3"	Straight Coupler with Air Vent  301V From: 15mm To: 15mm
Straight Coupler Burst pipe Repair  301BP From: 12mm To: 22mm	Male Straight Coupler  302 (\$302) From: 6 x 1/8" To: 108 x 4"	Extended Male Straight Connector with Back Nut  302B (\$302B) From: 15 x 1/2" To: 76 x 3"	Extended Male Straight Connector with Back Nut  302CB From: 15 x 1/2" x 38 To: 15 x 1/2" x 38	Male Taper Straight Connector  302TA (\$302TA) From: 10 x 3/8" To: 28mm	Straight Tap Connector  303SF (\$303SF) From: 15 x 1/2" To: 22 x 3/4"	Female Straight Connector for Pillar Tap  303ST From: 15mm To: 22mm
Tank Connector  321 (\$321) From: 15mm To: 54mm	Elbow  401 (\$401) From: 6mm To: 76mm	Reduced Elbow  401 RED (\$401RED) From: 12 x 10mm To: 28 x 22mm	Elbow with Drain Tap  401DA From: 15mm To: 28mm	Obtuse Elbow  401/O From: 15mm To: 28mm	Slow Bend  \$401S From: 15mm To: 28mm	Elbow with Air vent  401V From: 15mm To: 22mm
Male Elbow  402 (\$402) From: 8 x 1/4" To: 54 x 2"	Male Elbow with Drain Tap  402DA From: 15 x 1/2" To: 22 x 3/4"	Male Taper Elbow  402TA (\$402TA) From: 12 x 3/8" To: 28 x 1"	Female Elbow  403 (\$403) From: 8 x 1/4" To: 54 x 2"	Bent Tap Connector  403SF (\$403SF) From: 15 x 1/2" To: 22 x 3/4"	Female Wall Plate Elbow 2 Hole Flange  403W (\$403W) From: 12 x 1/2" To: 15 x 1/2"	Female Wall Plate Elbow 3 Hole Flange  403WL (\$403WL) From: 10 x 1/2" To: 22 x 3/4"
Tee - Equal  601EQ (\$601EQ) From: 6mm To: 76mm	Tee - Reduced Branch  601RB (\$601RB) From: 12 x 12 x 10mm To: 76 x 76 x 54mm	Tee - Reduced End  601REB (\$601REB) From: 15 x 12 x 12mm To: 28 x 22 x 22mm	Tee - Reduced Both Ends  601REE (\$601REE) From: 15 x 15 x 22mm To: 22 x 22 x 28mm	Tee with Male Branch  \$615 From: 15 x 15 x 1/2" To: 28 x 28 x 1"	Tee with Female Branch  617 (\$617) From: 12 x 12 x 3/8" To: 28 x 28 x 1"	Wall Plate Tee with Female Branch  \$617W From: 15 x 15 x 1/2" To: 22 x 22 x 1/2"
Tee with Male End  631 (\$631) From: 15 x 1/2" x 15 To: 22 x 3/4" x 22	Tee with Male Threaded End  645 From: 1/2" x 1/2" x 15 To: 1/2" x 1/2" x 15	Tee with Female End  684 (\$684) From: 15 x 1/2" x 15 To: 22 x 1/2" x 22	Stop End  323 (\$323) From: 8mm To: 54mm	Cross - Equal  901 From: 22 x 22 x 22 x 22 To: 22 x 22 x 22 x 22	S Code is for DZR fittings 	