



#### Certificate number: 2310830 (1)

lssued 19/12/2023 Expires 19/11/2028

# Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a) Model number(s) – see Appendix

### Watts Industries UK.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply. See <u>https://www.kiwa.com/gb/en/about-kiwa/water-products/</u> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec

(A Trading Division of Kiwa Ltd) 26A Rassau Industrial Estate Ebbw Vale Gwent NP23 5SD United Kingdom T +44 (0)1495 308185 uk.water@kiwa.com www.kiwa.co.uk Certificate Issued to: Watts Industries UK Colmworth Business Park St Neots PE19 8YX United Kingdom



## Product Certificate



#### Appendix to Certificate number: 2310830

#### The following products belong to this certificate

PRODUCT DESCRIPTION Y333 range of Y-strainers with blue epoxy coated cast iron bodies and stainless-steel strainer.
Y333 range of Y-strainers with blue epoxy coated cast iron bodies and stainless-steel strainer.
ATS3 – Without Production Surveillance.
MODEL(S)
Ref 3260
Ref 3261
Ref 3262
Ref 3263
Ref 3264
Ref 3265
Ref 3266
Ref 3267
Ref 3268
Ref 3269
SIZE:
See model.
SCOPE:
Manufacturer recommended maximum working pressure 16 Bar & maximum operating temperature 100°C.
Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.
MARKING
Socla on body.
MATERIALS
Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES
N/A.
ADDITIONAL NOTES
All water contact & exposed components satisfy opacity requirements.

Extra Notes