



Esimerkkikuva

OMINAISUUDET

- Puristusindikaattori
- Puristamattomana vuotava liitos

- Ulkopuoli sinkitty
- O-rengas mustaa CIIR-kumia
- Muhvipäissä läpikuultava suojatulppa

TEKNISET TIEDOT

Materiaali Seostamaton teräs 1.0034 E195
(EN 10305)

Tuotenro	LV/nro.	DN	d, ø mm	arc °	L cm	L1 cm	I cm	Z cm	Z1 cm
21001	0484023	10	12	90	5.6	3.5	2.8	1.1	1.8
21002	0484025	12	15	90	6.4	3.9	3.2	1.2	1.9
21003	0484028	15	18	90	6.8	4.1	3.4	1.4	2.1
21004	0484030	20	22	90	7.4	4.4	3.7	1.6	2.3
21005	0484032	25	28	90	8.4	5	4.2	1.9	2.7
21006	0484034	32	35	90	10	5.7	5	2.4	3.1

Tuotenro	LVI nro.	DN	d _g mm	arc °	L cm	L1 cm	I cm	Z cm	Z1 cm
21007	0484036	40	42	90	11.4	6.5	5.7	2.7	3.5
21008	0484038	50	54	90	13.8	7.7	6.9	3.4	4.2
21009	0484040	65	76.1	90	23	11	11.5	6.2	5.7
21010	0484042	80	88.9	90	26	12.7	13	7	6.7
21011	0484044	100	108	90	31	15.3	15.5	8	7.8