



Esimerkkikuva

OMINAISUUDET

- Puristusindikaattori
- Puristamattomana vuotava liitos
- Keskeinen
- O-rengas EPDM-kumia
- Puristuspäissä läpikuultava suojahattu

TEKNISET TIEDOT

Materiaali PPSU

Tuotenro	LV/nro.	DN	d, ø mm	d1, ø mm	L cm	Z cm
620.031.00.1	1752260	15, 12	20	16	8.4	1.9
620.032.00.1	1752261	20, 12	25	16	8.4	1.9
620.042.00.1	1752267	20, 15	25	20	8.4	1.9
620.003.00.1	1752590	25, 12	32	16	8.9	2
620.033.00.1	1752262	25, 15	32	20	8.9	2
620.043.00.1	1752268	25, 20	32	25	8.9	2

Tuotenro	LV:nro.	DN	d, ø mm	d1, ø mm	L cm	Z cm
620.034.00.1	1752263	32, 15	40	20	9.2	2.3
620.044.00.1	1752269	32, 20	40	25	8.9	2
620.054.00.1	1752273	32, 25	40	32	9.4	2.1
620.035.00.1	1752264	40, 25	50	32	12.2	2.7
620.045.00.1	1752270	40, 32	50	40	12.2	2.7
620.036.00.1	1752265	50, 32	63	40	12.9	3
620.046.00.1	1752271	50, 40	63	50	15.7	3.4
620.037.00.1	1752266	65, 32	75	40	13.6	3.7
620.047.00.1	1752272	65, 40	75	50	15.7	3.4
620.057.00.1	1752274	65, 50	75	63	16.2	3.5