



Esimerkkikuva

OMINAISUUDET

- Puristusindikaattori
- Puristamattomana vuotava liitos

- Lyijytön
- O-renkas EPDM-kumia
- Puristuspaissä läpikuultava suojahattu
- Kierrepäät läpikuultavalla suojahatulla

TEKNISET TIEDOT

Materiaali

Lyijytön piipronssi

Tuotenumero	LVI nro.	DN	d, ø mm	R "	L cm	H cm	SW mm
620.300.00.1	1752494	12, 10	16	3/8	6.1	2.8	18
620.310.00.1	1752362	12, 15	16	1/2	6.1	2.8	22
620.320.00.1	1752369	12, 20	16	3/4	6.5	3.2	27
620.301.00.1	1752495	15, 10	20	3/8	6.1	2.8	18
620.311.00.1	1752363	15	20	1/2	6.4	3.1	22
620.321.00.1	1752370	15, 20	20	3/4	6.5	3.2	27

Tuotenro	LV nro.	DN	d, ø mm	R "	L cm	H cm	SW mm
620.308.00.1	1752567	15, 25	20	1	6.4	3.1	34
620.302.00.1	1752356	20, 15	25	1/2	6.4	3.1	22
620.312.00.1	1752364	20	25	3/4	6.8	3.5	27
620.322.00.1	1752371	20, 25	25	1	6.6	3.3	34
620.309.00.1	1752568	25, 20	32	3/4	7.5	3.9	27
620.303.00.1	1752357	25	32	1	7.5	3.9	34
620.313.00.1	1752365	25, 32	32	1 1/4	7.2	3.6	43
620.304.00.1	1752358	32, 25	40	1	7.4	3.8	47
620.314.00.1	1752366	32	40	1 1/4	7.4	3.8	47
620.324.00.1	1752372	32, 40	40	1 1/2	7.3	3.7	49
620.305.00.1	1752359	40	50	1 1/2	10	4.1	59
620.315.00.1	1752367	40, 50	50	2	10.4	4.4	60
620.306.00.1	1752360	50	63	2	11	4.7	74

Tuotenro	LV:nro.	DN	d, ø mm	R "	L cm	H cm	SW mm
620.316.00.1	1752368	50,65	63	2 1/2	11.3	4.9	76
620.307.00.1	1752361	65	75	2 1/2	11.4	5	86