


Geberit Silent-db20 -haarayhde 45°



Esimerkkikuva



OMINAISUUDET

- Kulutuksenkestävä
- Erittäin hyvin ääntä eristävä
- UV-kestävä

TEKNISET TIEDOT

Varastointilämpötila	≤ 40 °C
Materiaali	PE-S2
Lämpölaajeneminen	0.17 mm/(m·K)

Putken lämmönjohtavuus

0.43 W/(m·K)

Tuotenro	LV/nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 maks. cm
305.054.14.1	2300593	56, 56	56	56	45	18	6	12	12	1.5
306.054.14.1	2300594	60, 56	63	56	45	19.5	6.5	13	13	2
306.064.14.1	2300595	60, 60	63	63	45	19.5	6.5	13	13	2
307.054.14.1	2300596	70, 56	75	56	45	21	7	14	14	3.5
307.064.14.1	2300597	70, 60	75	63	45	21	7	14	14	3
307.074.14.1	2300598	70, 70	75	75	45	21	7	14	14	2

Tuotenro	LVI nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 maks. cm
308.054.14.1	2300599	90, 56	90	56	45	24	8	16	16	5
308.064.14.1	2300600	90, 60	90	63	45	24	8	16	16	5
308.074.14.1	2300601	90, 70	90	75	45	24	8	16	16	4
308.084.14.1	2300602	90, 90	90	90	45	24	8	16	16	2.5
310.054.14.1	2300603	100, 56	110	56	45	27	9	18	18	7
310.064.14.1	2300604	100, 60	110	63	45	27	9	18	18	6.5
310.074.14.1	2300605	100, 70	110	75	45	27	9	18	18	5.5
310.084.14.1	2300606	100, 90	110	90	45	27	9	18	18	4.5
310.104.14.1	2300607	100, 100	110	110	45	27	9	18	18	3
312.104.14.1	2300608	125, 100	135	110	45	34.5	11.5	23	23	6.5
312.124.14.1	2300609	125, 125	135	135	45	34.5	11.5	23	23	5
315.144.14.1	2300612	150, 150	160	160	45	41.5	14	27.5	27.5	7