


Geberit PE -haarayhde 45°



Esimerkkikuva



OMINAISUUDET

- UV-kestävä

TEKNISET TIEDOT

Materiaali

PE-HD

Tuotenro	LV1 nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 maks. cm	K2 maks. cm	K3 maks. cm
379.108.16.1	2300848	30, 30	32	32	45	10.5	3.5	7	7	2	2	2
360.108.16.1	2300794	40, 30	40	32	45	13.5	4.5	9	9	3	3.5	3.5
360.109.16.1	2300795	40, 40	40	40	45	13.5	4.5	9	9	2.5	3	3
361.109.16.1	2300796	50, 40	50	40	45	16.5	5.5	11	11	4	4.5	4.5
361.112.16.1	2300797	50, 50	50	50	45	16.5	5.5	11	11	3.5	2	2
363.112.16.1	2300798	56, 50	56	50	45	18	6	12	12	4	3	3
363.115.16.1	2300799	56, 56	56	56	45	18	6	12	12	4	2.5	2.5

Tuotenro	LV nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 maks. cm	K2 maks. cm	K3 maks. cm
364.109.16.1	2300800	60, 40	63	40	45	19.5	6.5	13	13	4.5	4.5	4
364.112.16.1	2300801	60, 50	63	50	45	19.5	6.5	13	13	5	3	3
364.115.16.1	2300802	60, 56	63	56	45	19.5	6.5	13	13	4.5	2.5	2.5
364.120.16.1	2300803	60, 60	63	63	45	19.5	6.5	13	13	4	2	2
365.109.16.1	2300804	70, 40	75	40	45	21	7	14	14	6.5	5	6
365.112.16.1	2300805	70, 50	75	50	45	21	7	14	14	6	3	4
365.115.16.1	2300806	70, 56	75	56	45	21	7	14	14	5.5	2.5	3.5
365.120.16.1	2300807	70, 60	75	63	45	21	7	14	14	4.5	2.5	3.5
365.125.16.1	2300808	70, 70	75	75	45	21	7	14	14	4	2.5	2.5
366.109.16.1	2300809	90, 40	90	40	45	24	8	16	16	7.5	5.5	6.5
366.112.16.1	2300810	90, 50	90	50	45	24	8	16	16	8	4	5
366.115.16.1	2300811	90, 56	90	56	45	24	8	16	16	7.5	3.5	4.5
366.120.16.1	2300812	90, 60	90	63	45	24	8	16	16	7	3	4

<i>Tuotenro</i>	<i>LV nro.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 maks. cm</i>	<i>K2 maks. cm</i>	<i>K3 maks. cm</i>
366.125.16.1	2300813	90, 70	90	75	45	24	8	16	16	6.5	3	3.5
366.130.16.1	2300814	90, 90	90	90	45	24	8	16	16	5	2	2
367.109.16.1	2300815	100, 40	110	40	45	27	9	18	18	9.5	6	7.5
367.112.16.1	2300816	100, 50	110	50	45	27	9	18	18	9.5	5	5.5
367.115.16.1	2300817	100, 56	110	56	45	27	9	18	18	9	4	4.5
367.120.16.1	2300818	100, 60	110	63	45	27	9	18	18	8.5	3.5	4
367.125.16.1	2300819	100, 70	110	75	45	27	9	18	18	7.5	3	3.5
367.130.16.1	2300820	100, 90	110	90	45	27	9	18	18	6.5	2.5	3
367.135.16.1	2300821	100, 100	110	110	45	27	9	18	18	5.5	2	2
368.120.16.1	2300822	125, 60	125	63	45	30	10	20	20	10.5	4.5	6
368.125.16.1	2300823	125, 70	125	75	45	30	10	20	20	9.5	4	5
368.130.16.1	2300824	125, 90	125	90	45	30	10	20	20	8.5	3	3.5
368.135.16.1	2300825	125, 100	125	110	45	30	10	20	20	7	2.5	2.5

<i>Tuotenro</i>	<i>LV nro.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 maks. cm</i>	<i>K2 maks. cm</i>	<i>K3 maks. cm</i>
368.139.16.1	2300826	125, 125	125	125	45	30	10	20	20	6	2	2
369.125.16.1	2300827	150, 70	160	75	45	37.5	12.5	25	25	13.5	6.5	7.5
369.130.16.1	2300828	150, 90	160	90	45	37.5	12.5	25	25	12.5	5.5	6.5
369.135.16.1	2300829	150, 100	160	110	45	37.5	12.5	25	25	11	4.5	5.5
369.139.16.1	2300830	150, 125	160	125	45	37.5	12.5	25	25	10	4	5
369.145.16.1	2300831	150, 150	160	160	45	37.5	12.5	25	25	7.5	2.5	2.5
370.125.16.1	2300832	200, 70	200	75	45	54	18	36	36	8.5	10	2.5
370.135.16.1	2300833	200, 100	200	110	45	54	18	36	36	7.5	10	0
370.139.16.1	2300834	200, 125	200	125	45	54	18	36	36	5.5	9	0
370.145.16.1	2300835	200, 150	200	160	45	54	18	36	36	4	5.5	0
370.146.16.1	2300836	200, 200	200	200	45	54	18	36	36	0	0	0
371.135.16.1	2300837	250, 100	250	110	45	66	22	44	44	14	10	7.5
371.139.16.1	2300838	250, 125	250	125	45	66	22	44	44	13	13	6.5

Tuotenro	LV nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 maks. cm	K2 maks. cm	K3 maks. cm
371.145.16.1	2300839	250, 150	250	160	45	66	22	44	44	10.5	10	0
371.146.16.1	2300840	250, 200	250	200	45	66	22	44	44	7.5	0	1.5
371.147.16.1	2300841	250, 250	250	250	45	66	22	44	44	4	0	0
372.135.16.1	2300842	300, 100	315	110	45	84	28	56	56	23	20	16
372.139.16.1	2300843	300, 125	315	125	45	84	28	56	56	21.5	20	14.5
372.145.16.1	2300844	300, 150	315	160	45	84	28	56	56	19.5	17.5	12.5
372.146.16.1	2300845	300, 200	315	200	45	84	28	56	56	16.5	5	10
372.147.16.1	2300846	300, 250	315	250	45	84	28	56	56	13	5.5	6.5
372.148.16.1	2300847	300, 300	315	315	45	84	28	56	56	8.5	2	2