



Esimerkkikuva

## OMINAISUUDET

- Äänioptimoitu
- Kolmikerrospotki
- Putken sisäpuoli valkoinen

- Tiiviste EPDM-kumia
- Soveltuu varastoitavaksi ulkona kahden vuoden ajan

## TEKNISET TIEDOT

Asennuslämpötila	-10 – +40 °C
Materiaali	PP-C/PP-MD/PP-C
Lämpölaajeneminen	0.08 mm/(m·K)

Tuotenro	LV/nro.	DN	d <sub>e</sub> mm	d <sub>i</sub> mm	s mm	L cm	A <sup>2</sup> cm <sup>2</sup>
390.000.14.1	2409500	30	32	28	2	15	6.2
390.100.14.1	2409507	40	40	36	2	15	10.2
390.200.14.1	2409514	50	50	46	2	15	16.6
390.300.14.1	2409521	70	75	69.8	2.6	15	38.3
390.400.14.1	2409528	90	90	83.8	3.1	15	55.2
390.500.14.1	2409535	100	110	102.8	3.6	15	83

Tuotenro	LVI nro.	DN	d <sub>1</sub> ø mm	d <sub>2</sub> ø mm	s mm	L cm	A <sup>2</sup> cm <sup>2</sup>
390.600.14.1	2409542	125	125	116.6	4.2	15	106.8
390.700.14.1	2409549	150	160	149.6	5.2	15	175.8
390.001.14.1	2409501	30	32	28	2	25	6.2
390.101.14.1	2409508	40	40	36	2	25	10.2
390.201.14.1	2409515	50	50	46	2	25	16.6
390.301.14.1	2409522	70	75	69.8	2.6	25	38.3
390.401.14.1	2409529	90	90	83.8	3.1	25	55.2
390.501.14.1	2409536	100	110	102.8	3.6	25	83
390.601.14.1	2409543	125	125	116.6	4.2	25	106.8
390.701.14.1	2409550	150	160	149.6	5.2	25	175.8
390.002.14.1	2409502	30	32	28	2	50	6.2
390.102.14.1	2409509	40	40	36	2	50	10.2
390.202.14.1	2409516	50	50	46	2	50	16.6

Tuotenro	LVI nro.	DN	d <sub>1</sub> ø mm	d <sub>2</sub> ø mm	s mm	L cm	A <sup>2</sup> cm <sup>2</sup>
<b>390.302.14.1</b>	2409523	70	75	69.8	2.6	50	38.3
<b>390.402.14.1</b>	2409530	90	90	83.8	3.1	50	55.2
<b>390.502.14.1</b>	2409537	100	110	102.8	3.6	50	83
<b>390.602.14.1</b>	2409544	125	125	116.6	4.2	50	106.8
<b>390.702.14.1</b>	2409551	150	160	149.6	5.2	50	175.8
<b>390.004.14.1</b>	2409503	30	32	28	2	100	6.2
<b>390.104.14.1</b>	2409510	40	40	36	2	100	10.2
<b>390.204.14.1</b>	2409517	50	50	46	2	100	16.6
<b>390.304.14.1</b>	2409524	70	75	69.8	2.6	100	38.3
<b>390.404.14.1</b>	2409531	90	90	83.8	3.1	100	55.2
<b>390.504.14.1</b>	2409538	100	110	102.8	3.6	100	83
<b>390.604.14.1</b>	2409545	125	125	116.6	4.2	100	106.8
<b>390.704.14.1</b>	2409552	150	160	149.6	5.2	100	175.8

Tuotenro	LVI nro.	DN	d <sub>1</sub> ø mm	d <sub>2</sub> ø mm	s mm	L cm	A <sup>2</sup> cm <sup>2</sup>
390.005.14.1	2409504	30	32	28	2	150	6.2
390.105.14.1	2409511	40	40	36	2	150	10.2
390.205.14.1	2409518	50	50	46	2	150	16.6
390.305.14.1	2409525	70	75	69.8	2.6	150	38.3
390.405.14.1	2409532	90	90	83.8	3.1	150	55.2
390.505.14.1	2409539	100	110	102.8	3.6	150	83
390.605.14.1	2409546	125	125	116.6	4.2	150	106.8
390.705.14.1	2409553	150	160	149.6	5.2	150	175.8
390.006.14.1	2409505	30	32	28	2	200	6.2
390.106.14.1	2409512	40	40	36	2	200	10.2
390.206.14.1	2409519	50	50	46	2	200	16.6
390.306.14.1	2409526	70	75	69.8	2.6	200	38.3
390.406.14.1	2409533	90	90	83.8	3.1	200	55.2

Tuotenro	LV nro.	DN	d <sub>1</sub> ø mm	d <sub>2</sub> ø mm	s mm	L cm	A <sup>2</sup> cm <sup>2</sup>
<b>390.506.14.1</b>	2409540	100	110	102.8	3.6	200	83
<b>390.606.14.1</b>	2409547	125	125	116.6	4.2	200	106.8
<b>390.706.14.1</b>	2409554	150	160	149.6	5.2	200	175.8
<b>390.007.14.1</b>	2409506	30	32	28	2	300	6.2
<b>390.107.14.1</b>	2409513	40	40	36	2	300	10.2
<b>390.207.14.1</b>	2409520	50	50	46	2	300	16.6
<b>390.307.14.1</b>	2409527	70	75	69.8	2.6	300	38.3
<b>390.407.14.1</b>	2409534	90	90	83.8	3.1	300	55.2
<b>390.507.14.1</b>	2409541	100	110	102.8	3.6	300	83
<b>390.607.14.1</b>	2409548	125	125	116.6	4.2	300	106.8
<b>390.707.14.1</b>	2409555	150	160	149.6	5.2	300	175.8