


Geberit Silent-PP -kulmayhde



Esimerkkikuva



OMINAISUUDET

- Äänioptimoitu
- Tiiviste EPDM-kumia

TEKNISET TIEDOT

Asennuslämpötila -10 – +40 °C
 Materiaali PP-MD

Lämpölaajeneminen

0.08 mm/(m·K)

Tuotenumro	LV/nro.	DN	d, ø mm	arc °	X cm	Z cm	Z1 cm
390.020.14.1	2409606	30	32	15	5	0.6	1
390.120.14.1	2409607	40	40	15	5.4	0.7	1.1
390.220.14.1	2409608	50	50	15	5.8	0.7	1.1
390.320.14.1	2409609	70	75	15	6.5	0.9	1.5
390.420.14.1	2409610	90	90	15	7.3	1.2	1.7
390.520.14.1	2409611	100	110	15	8.2	1.4	2

Tuotenro	LVI nro.	DN	d, ø mm	arc °	X cm	Z cm	Z1 cm
390.620.14.1	2409612	125	125	15	8.8	1.4	2.3
390.720.14.1	2409613	150	160	15	9.7	1.7	2.6
390.021.14.1	2409614	30	32	30	5.2	0.8	0.9
390.121.14.1	2409615	40	40	30	5.7	0.9	1
390.221.14.1	2409616	50	50	30	6.2	1.1	1
390.321.14.1	2409617	70	75	30	7	1.5	1.5
390.421.14.1	2409618	90	90	30	7.9	1.8	1.7
390.521.14.1	2409619	100	110	30	9	2.1	2.2
390.621.14.1	2409620	125	125	30	9.8	2.4	2.5
390.721.14.1	2409621	150	160	30	11	3	2.8
390.022.14.1	2409622	30	32	45	5.5	1	1.1
390.122.14.1	2409623	40	40	45	6	1.2	1.3
390.222.14.1	2409624	50	50	45	6.5	1.5	1.4

Tuotenro	LVI nro.	DN	d, ø mm	arc °	X cm	Z cm	Z1 cm
390.322.14.1	2409625	70	75	45	7.6	2	2.1
390.422.14.1	2409626	90	90	45	8.5	2.4	2.5
390.522.14.1	2409627	100	110	45	9.7	3	2.9
390.622.14.1	2409628	125	125	45	10.7	3.3	3.3
390.722.14.1	2409629	150	160	45	12.2	4.2	4
390.023.14.1	2409630	30	32	67.5	5.9	1.5	1.5
390.123.14.1	2409631	40	40	67.5	6.5	1.8	1.8
390.223.14.1	2409632	50	50	67.5	7.2	2.1	2.1
390.323.14.1	2409633	70	75	67.5	8.6	3	3
390.423.14.1	2409634	90	90	67.5	9.7	3.6	3.5
390.523.14.1	2409635	100	110	67.5	11.2	4.4	4.3
390.623.14.1	2409636	125	125	67.5	12.3	4.9	4.9
390.723.14.1	2409637	150	160	67.5	14.3	6.2	6.1

Tuotenro	LVI nro.	DN	d, ø mm	arc °	X cm	Z cm	Z1 cm
390.024.14.1	2409638	30	32	87.5	6.4	1.9	2
390.124.14.1	2409639	40	40	87.5	7.1	2.3	2.5
390.224.14.1	2409640	50	50	87.5	7.9	2.8	3
390.324.14.1	2409641	70	75	87.5	9.7	4.1	4.2
390.424.14.1	2409642	90	90	87.5	11	4.9	4.8
390.524.14.1	2409643	100	110	87.5	12.8	6	6
390.624.14.1	2409644	125	125	87.5	14.2	6.8	6.7
390.724.14.1	2409645	150	160	87.5	16.6	8.5	8.4