


Geberit Silent-PP -haarayhde 45°



Esimerkkikuva

OMINAISUUDET

- Äänioptimoitu
- Tiiviste EPDM-kumia

TEKNISET TIEDOT

Asennuslämpötila -10 – +40 °C
 Materiaali PP-MD

Lämpölaajeneminen

0.08 mm/(m·K)

| Tuotenumro | LV/nro. | DN | d, ø mm | d1, ø mm | arc ° | H cm | Z1 cm | Z2 cm | Z3 cm |
|--------------|---------|--------|---------|----------|-------|------|-------|-------|-------|
| 390.030.14.1 | 2409647 | 30, 30 | 32 | 32 | 45 | 9.4 | 1 | 4 | 4 |
| 390.130.14.1 | 2409648 | 40, 30 | 40 | 32 | 45 | 9.7 | 0.6 | 4.6 | 4.4 |
| 390.131.14.1 | 2409649 | 40, 40 | 40 | 40 | 45 | 9.8 | 1.2 | 5 | 5 |
| 390.230.14.1 | 2409650 | 50, 30 | 50 | 32 | 45 | 10 | 0.1 | 5.3 | 4.9 |
| 390.231.14.1 | 2409651 | 50, 40 | 50 | 40 | 45 | 10.2 | 0.7 | 5.8 | 5.6 |
| 390.232.14.1 | 2409652 | 50, 50 | 50 | 50 | 45 | 12.7 | 1 | 6.3 | 6.3 |

| Tuotenro | LVI nro. | DN | d, ø mm | d1, ø mm | arc ° | H cm | Z1 cm | Z2 cm | Z3 cm |
|--------------|----------|----------|------------|-------------|----------|---------|----------|----------|----------|
| 390.331.14.1 | 2409653 | 70, 40 | 75 | 40 | 45 | 12 | 0.6 | 7.6 | 7 |
| 390.332.14.1 | 2409654 | 70, 50 | 75 | 50 | 45 | 13.4 | 0.1 | 8.1 | 7.6 |
| 390.333.14.1 | 2409655 | 70, 70 | 75 | 75 | 45 | 15 | 1.9 | 9.4 | 9.4 |
| 390.432.14.1 | 2409656 | 90, 50 | 90 | 50 | 45 | 13 | 0.6 | 9.1 | 8.4 |
| 390.433.14.1 | 2409657 | 90, 70 | 90 | 75 | 45 | 17.5 | 1.2 | 10.4 | 10.2 |
| 390.434.14.1 | 2409658 | 90, 90 | 90 | 90 | 45 | 19.6 | 2.2 | 11.3 | 11.3 |
| 390.531.14.1 | 2409659 | 100, 40 | 110 | 40 | 45 | 13.4 | 2.2 | 10.1 | 8.8 |
| 390.532.14.1 | 2409660 | 100, 50 | 110 | 50 | 45 | 14.8 | 1.5 | 10.6 | 9.5 |
| 390.533.14.1 | 2409661 | 100, 70 | 110 | 75 | 45 | 18.3 | 0.2 | 11.9 | 11.2 |
| 390.534.14.1 | 2409662 | 100, 90 | 110 | 90 | 45 | 20.3 | 1.3 | 12.6 | 12.2 |
| 390.535.14.1 | 2409663 | 100, 100 | 110 | 110 | 45 | 23.3 | 2.7 | 13.8 | 13.8 |
| 390.634.14.1 | 2409664 | 125, 90 | 125 | 90 | 45 | 21 | 0.6 | 13.6 | 12.9 |
| 390.635.14.1 | 2409665 | 125, 100 | 125 | 110 | 45 | 23.7 | 2.1 | 14.7 | 14.3 |

| Tuotenro | LV nro. | DN | d, ø mm | d1, ø mm | arc ° | H cm | Z1 cm | Z2 cm | Z3 cm |
|--------------|---------|----------|------------|-------------|----------|---------|----------|----------|----------|
| 390.636.14.1 | 2409666 | 125, 125 | 125 | 125 | 45 | 25.9 | 3.1 | 15.4 | 15.4 |
| 390.735.14.1 | 2409667 | 150, 100 | 160 | 110 | 45 | 24.5 | 0.4 | 17.2 | 16.1 |
| 390.736.14.1 | 2409668 | 150, 125 | 160 | 125 | 45 | 26.6 | 1.4 | 17.9 | 17.1 |
| 390.737.14.1 | 2409669 | 150, 150 | 160 | 160 | 45 | 31.5 | 3.9 | 19.6 | 19.5 |