


# Geberit Silent-PP -haarayhde 87,5°



Esimerkkikuva

## OMINAISUUDET

- Äänioptimoitu
- Tiiviste EPDM-kumia

## TEKNISET TIEDOT

Asennustemperatuuritila -10 – +40 °C  
 Materiaali PP-MD

Lämpölaajeneminen

0.08 mm/(m·K)

Tuotenro	LV/nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	Z1 cm	Z2 cm	Z3 cm
390.046.14.1	2409673	30, 30	32	32	87.5	8.2	1.7	2.1	2.1
390.147.14.1	2409674	40, 40	40	40	87.5	9.2	2.2	2.2	2.2
390.247.14.1	2409675	50, 40	50	40	87.5	9.5	2.2	2.8	2.2
390.248.14.1	2409676	50, 50	50	50	87.5	10.5	2.7	2.8	2.8
390.347.14.1	2409677	70, 40	75	40	87.5	10.4	2.3	4.2	2.6
390.348.14.1	2409678	70, 50	75	50	87.5	11.4	2.8	4.2	3.1

Tuotenro	LVI nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	Z1 cm	Z2 cm	Z3 cm
<b>390.349.14.1</b>	2409679	70, 70	75	75	87.5	13.9	4	4.3	4.3
<b>390.448.14.1</b>	2409680	90, 50	90	50	87.5	12.1	2.8	4.9	3.2
<b>390.449.14.1</b>	2409681	90, 70	90	75	87.5	14.6	4	5.1	4.5
<b>390.547.14.1</b>	2409682	100, 40	110	40	87.5	12.4	2.7	6	2.9
<b>390.548.14.1</b>	2409683	100, 50	110	50	87.5	12.9	2.8	6	3.2
<b>390.549.14.1</b>	2409684	100, 70	110	75	87.5	15.4	4	6.1	4.5
<b>390.650.14.1</b>	2409685	125, 90	125	90	87.5	17.1	4.6	6.9	5.2
<b>390.651.14.1</b>	2409686	125, 100	125	110	87.5	21.3	6.6	7.8	7.3
<b>390.652.14.1</b>	2409687	125, 125	125	125	87.5	20.6	6.4	6.8	6.8
<b>390.751.14.1</b>	2409688	150, 100	160	110	87.5	19.8	5.5	8.8	6.2
<b>390.752.14.1</b>	2409689	150, 125	160	125	87.5	21.3	6.4	8.7	6.9
<b>390.753.14.1</b>	2409690	150, 150	160	160	87.5	24.8	8.2	8.6	8.6