



Esimerkkikuva

OMINAISUUDET

- Massiivinen yksikerroksinen putki
- Erittäin hyvin ääntä eristävä
- Tiiviste EPDM-kumia

- Soveltuu varastoitavaksi ulkona kahden vuoden ajan

Materiaali
Lämpölaajeneminen

PP MX
0.08 mm/(m·K)

TEKNISET TIEDOT

Asennuslämpötila -10 – +40 °C

Tuotenro	LV/nro.	DN	d, ø mm	di, ø mm	s mm	L cm	A² cm²
393.210.14.1	2409803	50	50	44	3	50	15.2
393.310.14.1	2409804	70	75	67.4	3.8	50	35.7
393.410.14.1	2409805	90	90	81.4	4.3	50	52
393.510.14.1	2409806	100	110	101	4.5	50	80.1
393.610.14.1	2409807	125	125	115	5	50	103.9
393.211.14.1	2409808	50	50	44	3	100	15.2

Tuotenro	LV nro.	DN	d _g mm	d _i mm	s mm	L cm	A ² cm ²
393.311.14.1	2409809	70	75	67.4	3.8	100	35.7
393.411.14.1	2409810	90	90	81.4	4.3	100	52
393.511.14.1	2409811	100	110	101	4.5	100	80.1
393.611.14.1	2409812	125	125	115	5	100	103.9
393.213.14.1	2409813	50	50	44	3	200	15.2
393.313.14.1	2409814	70	75	67.4	3.8	200	35.7
393.413.14.1	2409815	90	90	81.4	4.3	200	52
393.513.14.1	2409816	100	110	101	4.5	200	80.1
393.613.14.1	2409817	125	125	115	5	200	103.9
393.214.14.1	2409818	50	50	44	3	300	15.2
393.314.14.1	2409819	70	75	67.4	3.8	300	35.7
393.414.14.1	2409820	90	90	81.4	4.3	300	52
393.514.14.1	2409821	100	110	101	4.5	300	80.1

Tuotenro	LVJ nro.	DN	d, ø mm	di, ø mm	s mm	L cm	A ² cm ²
393.614.14.1	2409822	125	125	115	5	300	103.9