


Geberit Silent-Pro -kulmayhde



Esimerkkikuva



OMINAISUUDET

- Erittäin hyvin ääntä eristävä
- Tiiviste EPDM-kumia

TEKNISET TIEDOT

Asennuslämpötila
Materiaali

-10 – +40 °C
PP MX

Lämpölaajeneminen

0.08 mm/(m·K)

Tuotenro	LV/nro.	DN	d, ø mm	arc °	X cm	Z cm	Z1 cm
393.220.14.1	2409823	50	50	15	5.8	0.7	1.1
393.320.14.1	2409824	70	75	15	6.5	0.9	1.5
393.420.14.1	2409825	90	90	15	7.3	1.2	1.6
393.520.14.1	2409826	100	110	15	8.2	1.4	2
393.620.14.1	2409827	125	125	15	8.9	1.6	2.4
393.720.14.1	2409828	150	160	15	9.9	1.9	2.7

Tuotenro	LV nro.	DN	d, ø mm	arc °	X cm	Z cm	Z1 cm
393.221.14.1	2409829	50	50	30	6.2	1.1	1
393.321.14.1	2409830	70	75	30	7.1	1.5	1.5
393.421.14.1	2409831	90	90	30	7.9	1.8	1.7
393.521.14.1	2409832	100	110	30	9	2.1	2
393.621.14.1	2409833	125	125	30	9.8	2.4	2.5
393.721.14.1	2409834	150	160	30	11	3	2.8
393.222.14.1	2409835	50	50	45	6.5	1.5	1.4
393.322.14.1	2409836	70	75	45	7.6	2	2.1
393.422.14.1	2409837	90	90	45	8.5	2.4	2.5
393.522.14.1	2409838	100	110	45	9.8	3	2.9
393.622.14.1	2409839	125	125	45	10.7	3.3	3.3
393.722.14.1	2409840	150	160	45	12.2	4.2	4
393.223.14.1	2409841	50	50	67.5	7.2	2.1	2.1

Tuotenro	LV nro.	DN	d, ø mm	arc °	X cm	Z cm	Z1 cm
393.323.14.1	2409842	70	75	67.5	8.6	3	3
393.423.14.1	2409843	90	90	67.5	9.7	3.6	3.5
393.523.14.1	2409844	100	110	67.5	11.2	4.4	4.3
393.224.14.1	2409845	50	50	87.5	7.9	2.8	3
393.324.14.1	2409846	70	75	87.5	9.7	4.1	4.2
393.424.14.1	2409847	90	90	87.5	11	4.9	4.8
393.524.14.1	2409848	100	110	87.5	12.8	6	6
393.624.14.1	2409849	125	125	87.5	14.2	6.8	6.7
393.724.14.1	2409850	150	160	87.5	16.6	8.5	8.4