


Geberit Silent-Pro Carve -haarayhde 87,5°



Esimerkkikuva



OMINAISUUDET

- Erittäin hyvin ääntä eristävä
- Tiiviste EPDM-kumia
- SuperTube-tekniologialla

TEKNISET TIEDOT

Asennuslämpötila	-10 – +40 °C
Materiaali	PP MX
Lämpölaajeneminen	0.08 mm/(m·K)

Tuotenro	LV/nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	Z1 cm	Z2 cm	Z3 cm
393.444.14.1	2409967	90, 50	90	50	87.5	12.9	5.4	8.9	1.4
393.445.14.1	2409968	90, 70	90	75	87.5	14.4	5.4	8.9	2.9
393.440.14.1	2409965	90, 90	90	90	87.5	16.9	7.9	10.4	2.9
393.544.14.1	2409976	100, 50	110	50	87.5	12.9	4.7	8.9	1.4
393.545.14.1	2409977	100, 70	110	75	87.5	15.2	5.2	8.9	3.2
393.541.14.1	2409973	100, 90	110	90	87.5	18.3	7.3	10.4	4.2

Tuotenro	LVJ nro.	DN	d, ø mm	d1, ø mm	arc °	H cm	Z1 cm	Z2 cm	Z3 cm
393.540.14.1	2409972	100, 100	110	110	87.5	21.2	9.2	10.7	5.2