


## NV Käyrä

Sektoreista valssattu ilmanvaihtokäyrä.  $r=1*d$ .


### NV 90°

| Nimellismitta<br>d (mm) | l<br>(mm) | l <sub>p</sub><br>(mm) | Paino<br>(kg) |
|-------------------------|-----------|------------------------|---------------|
| 250                     | 250       | 50                     | 1,7           |
| 315                     | 315       | 50                     | 3,6           |
| 400                     | 400       | 50                     | 6,9           |
| 500                     | 500       | 61                     | 10,1          |
| 630                     | 630       | 61                     | 15,0          |
| 800                     | 800       | 96                     | 27,0          |
| 1000                    | 1000      | 110                    | 47,0          |
| 1250                    | 1250      | 110                    | 64,0          |
| 1600                    | 1600      | 110                    | 116,0         |




### NV 60°

| Nimellismitta<br>d (mm) | l<br>(mm) | l <sub>p</sub><br>(mm) | Paino<br>(kg) |
|-------------------------|-----------|------------------------|---------------|
| 250                     | 146       | 50                     | 2,2           |
| 315                     | 184       | 50                     | 3,0           |
| 400                     | 234       | 50                     | 4,6           |
| 500                     | 292       | 61                     | 6,1           |
| 630                     | 367       | 61                     | 9,3           |
| 800                     | 466       | 96                     | 15,6          |
| 1000                    | 583       | 110                    | 29,0          |
| 1250                    | 728       | 110                    | 36,0          |
| 1600                    | 932       | 110                    | 83,0          |




### NV 45°

| Nimellismitta<br>d (mm) | l<br>(mm) | l <sub>p</sub><br>(mm) | Paino<br>(kg) |
|-------------------------|-----------|------------------------|---------------|
| 250                     | 105       | 50                     | 1,1           |
| 315                     | 130       | 50                     | 2,2           |
| 400                     | 165       | 50                     | 3,7           |
| 500                     | 205       | 61                     | 5,1           |
| 630                     | 260       | 61                     | 7,7           |
| 800                     | 330       | 96                     | 15,0          |
| 1000                    | 415       | 110                    | 24,0          |
| 1250                    | 520       | 110                    | 34,0          |
| 1600                    | 665       | 110                    | 63,0          |





### NV 30°

| Nimellismitta<br>d (mm) | l<br>(mm) | l <sub>p</sub><br>(mm) | Paino<br>(kg) |
|-------------------------|-----------|------------------------|---------------|
| 250                     | 70        | 50                     | 0,8           |
| 315                     | 85        | 50                     | 1,7           |
| 400                     | 110       | 50                     | 3,4           |
| 500                     | 135       | 61                     | 3,7           |
| 630                     | 170       | 61                     | 5,6           |
| 800                     | 215       | 96                     | 11,0          |
| 1000                    | 270       | 110                    | 17,0          |
| 1250                    | 335       | 110                    | 26,0          |



**NV 15°**

| Nimellismitta<br>d (mm) | l<br>(mm) | l <sub>p</sub><br>(mm) | Paino<br>(kg) |
|-------------------------|-----------|------------------------|---------------|
| 250                     | 33        | 50                     | 0,75          |
| 315                     | 51        | 50                     | 1,1           |
| 400                     | 53        | 50                     | 1,9           |
| 500                     | 66        | 61                     | 2,4           |
| 630                     | 83        | 61                     | 3,3           |
| 800                     | 105       | 96                     | 7,5           |
| 1000                    | 132       | 110                    | 13,0          |
| 1250                    | 165       | 110                    | 17,0          |



**Tuotemerkintä**

|              |       |           |       |          |       |          |       |          |
|--------------|-------|-----------|-------|----------|-------|----------|-------|----------|
|              |       | <b>NV</b> |       | <b>d</b> |       | <b>-</b> |       | <b>α</b> |
| Tuote        | _____ |           | _____ |          | _____ |          | _____ |          |
| Halkaisija d | _____ |           | _____ |          | _____ |          | _____ |          |
| Kulma α      | _____ |           | _____ |          | _____ |          | _____ |          |

**Esimerkki: NV 315-90**