



Technical datasheet

Brake Cleaner HP

Product description

Brake Cleaner HP is a powerful, fast-drying cleaner for brake and clutch parts.

Properties

- Cleans and degreases
- Leaves no residue
- Fast drying
- Does not corrode metals
- Prevents squeaking sounds
- Aerosol can be used in any angle (360°)



Applications

- Removes excess brake fluid, excess oil, dirt, etc. quickly.
- Prevents squeaking brakes and clutch slipping.

Technical data

Base	Hydrocarbon solvents
Consistency	Liquid
Density	Ca. 0.75 g/ml
Application temperature	+5°C → +35°C
Flashpoint	< 20°C
Volatile organic compounds (VOC)	97%

Substrates

- Substrate condition
Clean, free of dust and grease.
- Substrate types
Metals

Application method

- Application method
Shake can well before use. Spray sufficient product on the parts to be cleaned and let it work for a few seconds. If necessary, wipe clean with an absorbing cloth. In case of extensive carbon contamination, repeat the procedure. Do not use on rubber, plastics or painted parts. Test for adverse effects on the surface in advance. Make sure there is sufficient ventilation when using the product.

Health- and Safety Recommendations

Dangerous. Respect the precautions for use.

Use only in well-ventilated areas.

In case of contact with eyes, wash immediately with plenty of water.

Packaging/Logistics

Colour: Transparent



Brake Cleaner HP

Packaging: Please consult the product catalogue, the Soudal website or a Soudal representative.

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.