

ELECTRIC SERIES SCISSOR LIFTS

1932ME

Compliant with ANSI/CSA standards

PRODUCT HIGHLIGHTS

Efficient and Environmentally Friendly

- High work efficiency
- Environmental protections for zero emissions

Reduced Maintenance Costs

- Rapid and convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts

Reliable Performance

- Bumper rail protection



Standard Features

Maintenance-free battery	Automatic braking system	Drive at full height
Proportional control	Emergency lowering system	Forklift pocket and lifting eyes
Bumper rail	Emergency stop at both platform and ground controls	Electrophoresic paint technology
2WD x 2WS	Fault diagnosis system	Foldable guardrail
Non-marking tires	Tilt protection	Overload sensing system
Integrated hand shield	Automatic pothole guard	

Optional Features

Overhead anti-collision device	Headlight	RCBO
AC cable to platform	Foot switch	

SINOBOOM[™]
— NORTH AMERICA

PARTNERS IN ACCESS[™]

SINOBOOM.US | INFO@SINOBOOM.US
105 W RILEY ROAD, HOUSTON TX 77047

ELECTRIC SERIES SCISSOR LIFTS

1932ME

Compliant with ANSI/CSA standards

Model	1932ME
Dimensions	
Max Working Height	25' 7"(7.8m)
A-Max Platform Height	19'(5.8m)
B-Max Horizontal Extension	3'(0.9m)
C-Length Stowed	5' 11"(1.8m)
D-Width Stowed	2' 8"(0.81m)
E-Height Stowed (Rail Folded)	6' 2"(1.88m)
E-Height Stowed (Rail Unfolded)	7'(2.14m)
F-Wheelbase	4' 4"(1.33m)
Ground Clearance(Pothole Guard Stowed)	3"(75mm)
Ground Clearance (Pothole Guard Deployed)	0.95"(24mm)
Platform Dimensions(LxWxH)	5' 5" x 2' 6" x 3' 7"(1.64mx0.76mx1.1m)
Performance	
Platform Allowable Occupancy	2 persons(Indoor) 1 person (Outdoor)
Platform Capacity	507lbs(230kg)
Extension Platform Capacity	265lbs(120kg)
Drive Speed - Stowed	2.5mph(4km/h)
Drive Speed - Raised	0.5mph(0.8km/h)
Lift Time (Unloaded)	15s~20s
Descent Time (Unloaded)	25s~30s
Gradeability	25%
Turning Radius (Inside/Outside)	0' /4' 11"(0m/1.49m)
Tilt Rating (Front to Back/Side to Side)	3°/1.5°
Tire Size/Type	12.7x4"(323x100mm)/Solid
Power	
Batteries	4x6 V, 220 Ah
Power Source	24V DC
Drive Mode	Motor, Front Wheel
Charger Input	100~240V AC
Charger Output	30A
Hydraulic Tank Capacity	1.85 gal (US)(7L)
Weight	
Weight	3,473 lbs(1,575kg)

