

DESIGN &  
CONCEPT



MADE IN  
JAPAN

130TH ANNIVERSARY

**KATO**

## SKID LOADER AT35R

Bucket with  
floating function

Oversized filter  
180 L

Hydraulic pump  
in cast iron

Maximum HF flow rate  
135 L / min

Assisted  
cab lifting

Flag opening  
of the radiator



Digital  
controls



## COMPACT, POWERFUL AND RELIABLE

Warranty extension up to 5 YEARS with MAMOT programme

## DIMENSIONS AND LIFTING



<b>A</b> Maximum operating height with bucket fully raised	3847 mm
<b>B</b> Maximum height at pin with bucket fully raised	2775 mm
<b>C</b> Unloading height	2196 mm
<b>D</b> Maximum height unloading angle	43°
<b>E</b> Outreach at unloading with bucket at full height	701 mm
<b>F</b> Rollback angle of the bucket on the ground	32°
<b>G</b> Rear overhang	859 mm
<b>H</b> Pitch	1248 mm
<b>I</b> Bucket front overhang	1224 mm
<b>L</b> Max. length with std bucket	3330 mm
<b>M</b> Rear departure angle	30,3°
<b>N</b> Transport height	2063 mm
<b>O</b> Bucket width	1727 mm
<b>P</b> Gauge	1356 mm
<b>Q</b> Front clearance radius with std bucket	2039 mm
<b>R</b> Rear clearance radius	1515 mm
<b>S</b> Front clearance radius	1202 mm
<b>T</b> Track width	320 mm
<b>U</b> Width to tracks	1676 mm



# SPECIFICATIONS

GENERAL PERFORMANCE	
Operating weight	3672 kg
Weight when delivered with the bucket	3597 kg
Operating load	848 kg
Tipping load	2423 kg
Bucket cylinders breakout force	20.29 kN
ENGINE	
Engine manufacturer	HYUNDAI
Model	D24 Stage V
No. of cylinders and displacement	4 / 2392 cc direct injection
Rated output	55.4 kW / 2200 rpm
Maximum torque	320 Nm / 1600 rpm
Battery	12V 680A 74 Ah
Fuel consumption (100% - 70% rated output)	14.4 L / h - 10.5 L / h
Air Cooling / Supply	water / turbo intercooler
HYDRAULIC SYSTEM	
Maximum auxiliary system capacity	68.2 L / min
Maximum hydraulic circuit pressure	210 bar
Maximum Hi Flow system capacity	135 L / min
Max. Hi Flow system pressure	210 bar
Maximum travel speed	1° 6.8 km/h - 2° 10.9 km/h
BUCKET PERFORMANCE	
Standard bucket width	1727 mm
Levelled bucket capacity	0.3 m³
Full bucket capacity	0.4 m³
Levelled load mass (mat. density 2000kg/m³)	600 kg
Full load mass (mat. density 2000kg/m³)	800 kg
CAPACITY	
Engine oil	8.6 L
Cooling system	9 L
Fuel tank capacity	64 L
Hydraulic tank capacity	38 L
OTHER DATA	
Sound power level (outside)	103 dB
ROPS structure	compliant with EN 3471
FOPS structure	compliant with EN 3449 Lev. I
Tracks	320x86x48 mm
Throttle control	manual (display/potentiometer)

## Facilitated maintenance, in safety and in every situation:

hydraulically assisted cab and boom lift even at a standstill.







# DOTAZIONI

FRAME	
Rear security door	●
4 lifting points and transport anchors set-up	●
Mechanical locking device of the lifting arm	●
Road circulation validation kit	○
ENGINE	
Air filter with double filtrating element and clogging electrical indicator	●
Air-water-oil radiator with openable hinged water expansion tank	●
Buzzer and reverse alarm	●
HYDRAULIC SYSTEM	
Brakes and transmission locking system	●
Pilot-operated hydrostatic transmission	●
Negative hydraulic parking brake on both traction engines	●
Oil filter with clogging indicator	●
Arm "float" function	●
Aux. hydraulic system Two-way	●
Aux. hydraulic system HF	●
Dual advance speed	●
Self-levelling system of accessories during arm lifting	●
CAB SPACE	
Tipping cab compliant with standard CE ROPS-FOPS Level I	●
Front cab-door glass closing kit with wipers and washing system	○
Heating system kit	○
Air conditioning kit	○
FOPS Level II	○
Internal ceiling light fixture	●
Rear, removable window for safety exit	●
Handles for ascent	●
Auxiliary 12V outlet	●
DRIVER'S SEAT	
Safety bar with arm support	●
Adjustable spring seat	●
Adjustable, self-winding seat belt	●
Pilot-operated hydraulic joystick controls	●
Removable cover to clean the floor	●
INSTRUMENTS AND CONTROL	
Indicators: fuel level-engine water temperature	●
Hour meter	●
Key ignition	●
Warning lights: engine coolant temperature, hydraulic oil temperature, engine oil pressure, battery charge, glow plug preheating	●
Air filter clogging control warning light	●
Hydraulic oil filter clogging control warning light	●
Floating on-off switch	●
Parking brake on-off switch	○
Front and rear work light switch	●
Rear windscreen wiper switch	●
ACCESSORIES	
Accessories self-levelling kit (ascent)	●
Foot throttle kit	○
Pallet fork	○
Snowplough blade	○
Sweeper with collection bucket	○
Industrial sweeper	○
Mixing bucket	○
Asphalt milling cutter	○
4-in-1 dosing blade	○
Adjustable blade	○

● standard ○ optional



# SINCE 1895: ALL-ROUND



# KATO



**KATO IMER S.p.A.**

53037 San Gimignano (SI) Loc. Cusona - Italy  
Phone: +39 0577 951 21 - Fax: +39 0577 982 400  
info@katoimer.com | www.katoimer.com