**Specifications**

Partner	Mayer
Contents	100% polyester
Repeat	None
Weight	15 oz./lin. yd.
Width	54"

Performance


Abrasion	100,000 double rubs
Flammability	NFPA 260/UFAC Class 1, ASTM E84 (unadhered) Class 1 or A, California Technical Bulletin 117-2013
Lightfastness	40 hours, Grade 4 minimum
Crocking	Dry and wet: Class 4 minimum
Breaking Strength	Warp: 290 lbs. Weft: 239 lbs.

Sustainability

GREENGUARD Gold Certified for low chemical and particle emissions to UL standard UL 2818. This fabric may contribute to LEED certification.

For more information including application options, please visit [inscapesolutions.com](https://www.inscapesolutions.com).

Fedora



AEGEAN
U1583



AQUAMARINE
U1584



BITUMEN
U1585



CACTUS
U1586



CHARCOAL
U1587



CITRON
U1588



DAPPER
U1589



DEW
U1590



ESPRESSO
U1591



EUCALYPTUS
U1592



FAWN
U1593



INDIGO
U1594




LIGHT GREY
U1595



MIDNIGHT
U1596



MINK
U1597



OPAL
U1598



PERSIMMON
U1599




PEWTER
U1600




PLUMBERRY
U1601



PURPLE
U1602



RUBY
U1603



TANGELO
U1604



TOMATO
U1605



TOPAZ
U1606



WINTER
U1607