 <b>FIXFAST</b>	<b>Declaration of Performance (DoP)</b>
<b>Seelex Hybrid Construction</b>	<b>N° 010_seelex_0219</b> (In accordance with annex III of the EU regulation 305/2011)

1. Unique identification code of the product-type:

**Seelex Hybrid Construction Sealant**

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

**Batch number: See entry on packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealant for facade application exterior and interior –  
Conform EN 15651-1:2012 Type F EXT-INT**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Fixfast Ltd  
Merlin House  
Seven Mile Lane  
Borough Green, Sevenoaks  
TN15 8QY, UK  
(T) 0800 304 7616**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2) :

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:


**System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**The notified body 4ward Testing Ltd, identification number NB 2538,  
performed the determination of the product type based on type testing under system 3  
and issued: a test report**

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

**Not applicable**

 <b>FIXFAST</b>	<b>Declaration of Performance (DoP)</b>
<b>Seelex Hybrid Construction</b>	<b>N° 010_seelex_0219</b> (In accordance with annex III of the EU regulation 305/2011)

9. Declared Performance:

Essential characteristics	Performance	Technical harmonised specification
Reaction to fire (classification according EN 13501-1:2007)	Class E	-
Release of chemicals dangerous to the environment and health	See SDS	-
<b>Water and air tightness</b>		
Resistance to flow (according EN ISO 7390)	≤ 3mm	EN 15651-1:2012
Loss of volume (according EN ISO 10563)	≤ 10 %	EN 15651-1:2012
Tensile properties for “non-structural” low modulus sealants used in joints in “cold climate” areas (-30 °C) – according EN ISO 8339	NPD	EN 15651-1:2012
Tensile properties for “non-structural” sealants used in joints in “cold climate” areas (-30 °) at maintained extension – according EN ISO 8340	NPD	EN 15651-1:2012
Tensile properties · after immersion in water (according EN ISO 10591) · at maintained extension after water immersion (according EN ISO 10590)	NPD	EN 15651-1:2012
Durability Pass EN 15651-1:2012	NPD	EN 15651-1:2012

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by



Jack Mumford  
Quality Manager  
February 2019