



SureFast® SF-RIV Peel Rivets

Peel rivets for fastening insulation and membrane in flat roofing applications

Application

For fastening insulation and membrane to thin metal decking materials and difficult substrates such as woodwool slab in conjunction with SureFast pressure plates

Key Features

- Aluminium body with zinc-plated steel pin
- Body "peels" as pin is withdrawn providing a spread of surface area on the underside to prevent pullout or break up of substrate

Datasheet

01 FASTENER SYSTEMS
SureFast RIV rivets

SureFast RIV Peel rivets

Specification	
Rivet body	Aluminium alloy (ALMG 3.0/ 5.0)
Rivet mandrel	Carbon steel - Zinc-plated - CR VI free

Installation and handling	
Installation tool	Cordless power riveter
Correct installation	Fasteners should be driven within three degrees of perpendicular to the surface of the fastened material. Avoid over-driving, and do not over-tighten.
Handling	Fasteners may have sharp edges, and the use of power tools can be dangerous. Use personal protective equipment. Do not allow uninstalled fasteners to become wet or store in damp conditions. Inspect each fastener before use and do not use damaged fasteners. Replace any fasteners which appear to have been installed incorrectly.

Installation Recommendations

Recommended pilot hole usually 7.0mm diameter, depending on site conditions. Please note: For all applications a site pull-out test is recommended.

Code	Max build-up (mm)
SF-RIV 6.3 x 50	25
SF-RIV 6.3 x 100	75
SF-RIV 6.3 x 125	100
SF-RIV 6.3 x 150	125
SF-RIV 6.3 x 175	150
SF-RIV 6.3 x 200	175
SF-RIV 6.3 x 250	225



FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0800 304 7616 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.

The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

