



Resin anchor tools and accessories

Application

- For use with resin chemical anchor system

Key Features

- Complete kit of products to provide secure fixings in all applications

Resin anchor tools and accessories


Product	Base material				
	Concrete	Damp concrete	Solid brick	Hollow brick	Aircrete
FIS-H	-	-	-	✓✓	-
PBZ	-	-	-	-	✓✓
PBB	-	-	-	-	✓✓
FIS-BS	✓✓	✓✓	✓✓	✓✓	✓✓
ABG	✓✓	✓✓	✓✓	✓✓	✓✓

✓✓ = Recommended for use

Code	Description	To fit size (mm)	Drill size (mm)	Drill depth (mm)	Max fixing thickness (mm)
FIS-H-16 x 85N	Anchor sleeves allow secure fixing into hollow or perforated substrates without wastage	M8	16	95	85
FIS-H-18 x 85N		M10	18	95	85
FIS-H-20 x 85N		M12	20	95	85
PBZ	Ensures secure RGM rod placing	Suits all RGM rods from M8 to M12			
FIS SITE BOX	Includes tool box, brush set, 1 blow out pump, 1 Bi-Axial cartridge gun, 5 static mixer nozzles				
PBB	SDS drill forms conical hole in suitable substrates, adjustable drill depth 75-95mm	To suit RGM rod M8 to M12			
FIS-BS	Includes 14mm and 20mm brush to clear sediment				
FIS-AK	To suit Bi-Axial cartridge resin FIS-360S				
ABG	For cleaning sediment from hole before installation				



FIS-H



PBZ



FIS SITE BOX



PBB



FIS-BS



FIS-AK



ABG

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007