



DuraMet®

Fixed and shingle cleats

Application

- For fully supported metal roofing systems

Key Features

- Manufactured from A2/304 grade stainless steel for optimum corrosion resistance
- Supplied with pre-punched flat or countersunk holes
- Available to suit variety of seam heights

Datasheet

Document Reference: DS-FS-DMF-7.17/01

01 FASTENER SYSTEMS
DuraMet® fixed and shingle
cleats

DuraMet® Fixed and shingle cleats

Code	To suit seam height (mm)	Gauge (mm)	Hole type
DM-04-25-F	25	0.4	Flat
DM-04-25-F-CSK	25	0.4	Countersunk



DM-04-F-CSK

Code	Individual bearing load (kN)	Shared bearing load (kN)
FIXED CLEAT	0.65	0.40

Code	Gauge (mm)	Hole type
DM-04-SHINGLE	0.4	Flat



DM-04-SHINGLE

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007