



TufFast™

Masonry fasteners

Application

Simple one piece method for fastening to masonry.

Key Features

- One piece masonry anchor no plugs or inserts
- Versatile range countersunk or 8mm hex combo head styles
- Available with safeseal bonded washers for excellent weather sealing
- Can be colour capped or lacquered to match sheet material
- Special thread form provides high pull-out strength into concrete block, hollow block, brick and other masonry materials

Datasheet

01 FASTENER SYSTEMS TufFast™ Masonry fasteners

TufFast™ Masonry fasteners

			Build-up				
Code	Head style	Fastener length (mm)	Concrete block		Brickwork		
			Unwashered	A15/A19	Unwashered	A15/A19	
HTF-6.3 X 32	8mm Hex head Slotted Phillips combo head	32	0-7	0-5	N/A	N/A	
HTF-6.3 X 45		45	0-20	0-18	0-10	0-8	
HTF-6.3 X 57		57	0-32	0-30	0-22	0-20	
HTF-6.3 X 70		70	0-45	0-43	0-35	0-33	
HTF-6.3 X 82		82	0-57	0-55	0-47	0-45	
HTF-6.3 X 100		100	0-75	0-73	0-65	0-63	
HTF-6.3 X 125		125	0-100	0-98	0-90	0-88	
HTF-6.3 x 150		150	0-125	0-123	0-115	0-113	

Washer options









	Head style	Fastener length (mm)	Build-up			
Code			Concrete block		Brickwork	
			Unwashered	A15/A19	Unwashered	A15/A19
CTF-6.3 X 45	Countersunk no.3 Phillips	45	0-20	N/A	0-10	N/A
CTF-6.3 X 57		57	0-32		0-22	
CTF-6.3 X 70		70	0-45		0-35	
CTF-6.3 X 82		82	0-57		0-47	
CTF-6.3 X 100		100	0-75		0-65	

For fastening to masonry a pilot hole is required - normally 4.8mm/5.0mm diameter

Recommended minimum fastener embedment:

Concrete block 25mm

Brickwork 35mm

Includes 1 FOC TCT drill bit per 100 fixings to suit electric percussion drills with a standard chuck

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com



Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.

The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY