



Stainless steel countersunk woodscrews

Application

- For fastening to timber in corrosive environments

Key Features

- A2/304 stainless steel for optimum corrosion resistance
- Ribbed double countersunk head increases strength
- Improved countersinking performance into timber

Datasheet

Document Reference: DS-FS-SSCW-7.17/01

01 FASTENER SYSTEMS
Stainless steel countersunk
woodscrews

Stainless steel countersunk woodscrews

Code	Diameter (mm)	Length (mm)	Drive bit	Boxed in
CWS-SS-4 x 25	4	25	2-PZD	200
CWS-SS-4 x 30	4	30	2-PZD	200
CWS-SS-4 x 40	4	40	2-PZD	200
CWS-SS-4 x 50	4	50	2-PZD	200
CWS-SS-4 x 70	4	70	2-PZD	200
CWS-SS-5 x 25	5	25	2-PZD	200
CWS-SS-5 x 30	5	30	2-PZD	200
CWS-SS-5 x 40	5	40	2-PZD	200
CWS-SS-5 x 50	5	50	2-PZD	200
CWS-SS-5 x 70	5	70	2-PZD	200
CWS-SS-5 x 100	5	100	2-PZD	100



CWS-SS

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007