



Galvanised perforated Banding

Application

• For clamping, fixing and supporting pipes, ducting, cables, joists

Key Features

- Excellent flexibility means it can be easily formed to any shape
- Supplied in plastic dispensing cassette
- Supplied in 10m long rolls and simply cut to the required length
- Economic and simple fixing solution

Document Reference: DS-FS-GPB-7.17/01

Datasheet

01 FASTENER SYSTEMS Galvanised perforated banding

Code	Roll width (mm)	Roll length (m)	Thickness (mm)	Hole size (mm)
VL1210G	12	10	0.8	5
VL1710G	17	10	0.8	7
VL2610G	26	10	1	8



FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com



Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218. The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.

Certificate Number 10905 ISO 9001: 2008 ISO 14001: 2004 BS OHSAS 18001: 2007