



Ultra high bond tape

Application

- Suitable for use as a temporary fix when used in conjunction with structural bonding adhesives

Key Features

- When used with UHB PRIMER, provides a high strength bond within minutes of application
- Good UV resistance

Ultra high bond tape

Code	Roll thickness (mm)	Roll width (mm)	Roll length (m)	Rolls per carton	Colour
UHB-1.2 x 25 x 33	1.2	25	33	24	Grey
UHB PRIMER	For priming substrates prior to applying UHB-1.2 x 25 x 33				



UHB

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007