



Temporary Downpipe

Temporary falling water control

Application

- Temporary downpipe to control the flow of water where full guttering systems are not completed

Key Features

- Lightweight solution to control falling water
- Available in kit form
- Re-useable
- One roll provides 100m of downpipe

Datasheet

Document reference: DS-RDS-TD-7.17/01

Temporary Downpipe

Temporary Downpipe				
Code	Tube diameter (mm)	Roll length (m)	Stainless banding kit	Roll of CDT-50
TD-200 x 100	200	100	x	x
TD-200 x 100-KIT			✓	✓



TD-200 x 100-KIT

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007