

PaveProp™

Paving supports

Application

- Designed to allow concealed drainage below paving slabs

Key Features

- Supports incorporate raised spacers to maintain open drainage gaps between slabs
- Available in rubber or injection moulded polypropylene
- Special shims available for fine height adjustment
- The polypropylene version can be stacked to allow variable space beneath paving

Datasheet

Document Reference: DS-RP-PS-7.17/01

04 ROOFTOP PRODUCTS
PaveProp™ Paving supports

PaveProp™ Paving supports


code	Material	Diameter (mm)	Height (mm)
PSR-1	Rubber	120	9.00
PS-1	Polypropylene	150	15
PS-SHIM	Polypropylene	150	3



PSR-1



PS-1



PS-SHIM

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007