

Maximum reliability. Minimum fuss.



Technical Data Sheet

Sealex BR

Sealing Products



Butyl rubber sealant.

Application

- + Sealex BR sealant can be used for a variety of sealing applications within the construction industry
- + Suitable for flashing, butt strap joints and bedding applications

Key Features

- + High quality solvent release bedding sealant
- + Manufactured from butyl rubber blended with fillers and polymers
- + Long service life - 15 years or more expected
- + No staining or oil bleed
- + Very flexible/non-hardening at low temperature
- + Excellent adhesion
- + Low shrinkage

Substrate compatibility

| Steel | Aluminium | GRP / PVC | Fibre cement | Glass (uncoated) | Timber (painted or stained) | Concrete / Brickwork | Bitumen | Lead |
|-------|-----------|-----------|--------------|------------------|-----------------------------|----------------------|---------|------|
| ✓* | ✓* | ● | ● | - | ● | ○ | - | - |

✓* = Recommended for airseal decks, not outer sheet ● = Compatible ○ = Possible

Limitations

Seelex BR Sealant must not be used in:-

- Constant water immersion situations
- Exposed joints
- In contact with the edge of laminated glass or insulating glass units

Specification

| Code | Cartridge size (ml) | Cartridges per carton | Colour |
|-----------------|---------------------|-----------------------|--------|
| SEELEX BR GREY | 380 | 25 | Grey |
| SEELEX BR WHITE | 380 | 25 | White |



Application Instructions

General

All surfaces must be clean and dry and free from dirt, dust, grease and other contamination. The sealant should be applied by applicator gun, firmly onto the surface to ensure good contact and adhesion.

After application the sealant should not be left too long before the surfaces are combined and mechanically fixed.

Sealant extruded from the joint can be wiped off and the surface cleaned with white spirit.

Storage

Store in cool dry conditions.

Health & Safety

The sealant is flammable and contains organic solvent. Keep away from sources of ignition. Use in well ventilated areas.

Should any of the sealant come into contact with eyes, then flush eyes liberally with clean water. Seek medical advice if irritation persists. If accidentally ingested, see medical attention. See Health & Safety Data Sheet for further information.

Further Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. Each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Estimating quantities

The figures given in these charts are the number of linear metres obtained from a cartridge for rectangular joints. These figures are only approximate and do not allow for wastage.

| 310ml cartridge | | | | | | |
|-----------------|---|------------|------|------|------|-----|
| Joint size | | Width (mm) | | | | |
| | | 3 | 6 | 9 | 12 | 15 |
| Depth (mm) | 3 | 44.4 | 22.2 | 14.8 | 11.1 | 8.9 |
| | 6 | 22.2 | 11.1 | 7.4 | 5.6 | 4.4 |
| | 9 | 14.5 | 7.4 | 4.9 | 3.7 | 3.0 |



Merlin House
Seven Mile Lane
Borough Green
Sevenoaks
Kent
TN15 8QY

Enquiries

0800 304 7616

International

+44 (0) 1732 882387

Fax

0845 450 7486

Email

info@fixfast.com



Certificate number 10905
ISO 9001, ISO 14001
ISO 45001