



# Seelex FR

Fire rated sealant

## Applications

- Sealant for firewall applications
- For bedding in uncoated glass in fire doors etc

## Key Features

- Acrylic based intumescent sealant
- Provides up to 4 hours fire resistance
- Conforms to BS474 Part 20 and ISO 11600 classification F12-SP
- Can be painted

# Seelex FR Fire rated sealant

## Substrate compatibility

Steel	Aluminium	GRP / PVC	Fibre cement	Glass (uncoated)	Timber (painted or stained)	Concrete / Brickwork	Bitumen	Lead
✓	✓	✓	●	✓	✓	✓	-	✓

✓ = Recommended ● = Compatible

Code	Cartridge size (ml)	Cartridges per carton	Colour
SEELEX FR	310	25	White

SEELEX FR



Gap face material combination	Width (mm)	Depth (mm)	Backing material	Integrity (minutes)	Insulation (minutes)
Aerated blockwork / Aerated blockwork	50	25	Backing rod 50mm diameter	245	82
Hardwood / aerated blockwork	50	25		96	93
Softwood / aerated blockwork	25	12		55	54
Steel / aerated blockwork	50	25		77	39
Aerated concrete / aerated concrete	50	25		155	105
Hardwood / aerated concrete	50	25		47	47
Softwood / aerated concrete	25	12		51	44
Steel / aerated concrete	50	25		72	62

## Estimating quantities

The figures given in these charts are the number of linear metres obtained from a cartridge for rectangular joints. These figures are only approximate and do not allow for wastage.

310ml cartridge						
Joint size	Width (mm)					
	3	6	9	12	15	
Depth (mm)	3	34.4	17.2	11.5	8.6	6.9
	6	17.2	8.6	5.7	4.3	3.4
	9	11.5	5.7	3.8	2.9	2.3

Movement %	UV resistance	Service temperature °C	Application temperature °C
25	Excellent	-40 to +120	+5 to +30

**FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY**  
**T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com**

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218. The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

*©Fixfast July 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.*



Certificate Number 10905  
 ISO 9001: 2008  
 ISO 14001: 2004  
 BS OHSAS 18001: 2007