



Foilband

Application

- For flashing and repair

Key Features

- Compatible with most building materials including: metals, glass and plastics such as polycarbonates, polyacrylate and PVCu
- High tack, high strength butyl strip sealant laminated to a UV resistant plastic foil
- Excellent adhesive properties even at low temperatures
- Resistant to water vapour transmission

Foilband

Substrate								
Tape	Steel	Aluminium	GRP / PVC	Fibre cement	Glass (uncoated)	Timber (painted or stained)	Fire resisting	Gutter joints
Foilband	√	√	●	●	√	●	-	○

√ = Recommended ● = Compatible ○ = Possible

Code	Roll width (mm)	Roll length (m)	Rolls per carton	Colour
FOILBAND-50	50	10	6	Silver foil on white butyl
FOILBAND-100	100	10	4	



FOILBAND

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast July 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007