



# **Blades**

For reciprocating saws and jigsaws

### **Application**

 Cutting blades for cutting anything from timber and metal to fibre cement

### **Key Features**

- High quality brands to ensure longevity
- specific blade types to cope with any construction situation



08 SPECIALIST TOOLS Blades for reciprocating saws and jigsaws

## **Blades for reciprocating saws and jigsaws**

### **Reciprocating saw blades**

Code	Blade length (mm)	Working length (mm)	Teeth per inch (mm)	Suggested application	Blades per pack
RSB-M-100-24	100	35	24	All metals less than 3.2mm thick	5
RSB-M-150-24	150	85	24	All metals less than 3.2mm thick	5
RSB-M-200-18	200	135	18	Structural steel, stainless steel (1.5 - 5.0mm thick) non-ferrous metal (1.5 - 8.0mm thick)	5
RSB-MW-200-10	200	135	10	Nail embedded wood, plastics, carbon steel Stainless steel (3.2 - 6.0mm thick) non-ferrous metal (3.2 - 13.0mm thick)	5
RSB-MW-300-10	300	235	10/14	Nail embedded wood, plastics, carbon steel stainless steel (3.2 - 6.0mm thick) non-ferrous metal (3.2 - 13.0mm thick)	5
RSB-MW-150-6	150	85	6	Fast cutting for wood, plastics and non-ferrous metals	5
RSB-MW-300-6	300	235	6	Nail embedded wood, fast cutting, structural steel, stainless steel and non-ferrous metal (more than 5mm thick)	5
RSB-FC-300-2	300	225	Medium carbide grit	for cutting fibre cement panels	1



### **Jigsaw blades**

Code	Blade length (mm)	Working length (mm)	Teeth per inch (mm)	Suggested application	Blades per pack
JB-M-126-21	126	100	21	Mild steel and non-ferrous metal 1.5 - 4.0mm	5
JB-W-101-6	101	75	6	Wood (very clean cut), blockboard, chipboard, plywood and plastics	5
JB-M-76-36	76	50	36	Mild steel and non-ferrous metal up to 2mm	5
JB-M-76-13	76	50	13	Mild steel and non-ferrous metal 3.0 - 6.0mm	5
JB-M-101-8	101	75	8	Mild steel 3.0 - 6.0mm and non-ferrous metal 3.0 - 15.0mm	5
JB-M-76-21	76	50	21	Mild steel and non-ferrous metal 1.5 - 4.0mm Narrow blader for cutting curves	5



FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0800 304 7616 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

