



RGM

Resin anchor threaded rods

Application

- Fastening of materials to primary substrate in conjunction with resin

Key Features

- Zinc plated steel complete with washer and hex nut
- External drive for direct installation with capsules
- Suitable for all resin systems
- Includes free drive bit

Datasheet

Document Reference: [DS-FS-RGM-7.17/01](#)

01 FASTENER SYSTEMS
RGM resin anchor
threaded rods

RGM resin anchor threaded rods

Fastener	Base material				
	Concrete	Damp concrete	Solid brick	Hollow brick	Aircrete
RGM	✓✓	✓✓	✓✓	✓✓	✓✓

✓✓ = Recommended for use

Code	Thread diameter (mm)	Length (mm)	Minimum anchorage depth (mm)	Max fixing thickness (mm)	Nut size (mm)	Drill diameter (mm)
RGM8 x 110	M8	110	80	13	13	10
RGM8 x 150	M8	150	80	60	13	10
RGM10 x 130	M10	130	90	20	17	12
RGM10 x 165	M10	165	90	57	17	12
RGM10 x 190	M10	190	90	82	17	12
RGM12 x 160	M12	160	110	25	19	14
RGM12 x 220	M12	220	110	90	19	14
RGM12 x 250	M12	250	110	120	19	14
RGM16 x 165	M16	165	125	13	24	18
RGM16 x 190	M16	190	125	35	24	18
RGM16 x 250	M16	250	125	98	24	18
RGM16 x 300	M16	300	125	148	24	18



RGM16

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007