

Maximum reliability. Minimum fuss.



Technical Data Sheet



UV120 Facade Membrane

Weatherproofing Products

Application

- + For use in open facade installations behind metal and wooden facades, with gaps of up to 30mm

Key Features

- + For metal and wooden facades
- + Highly Resistant to UV exposure
- + Flame Retardant
- + Breathable to allow escape of moisture
- + Moisture proof preventing rain penetration
- + Hydrophobic (water-repellent)
- + Optional self-adhesive edges for rain and windproof overlaps
- + Compatible with all substrates
- + 10 year guarantee

Products

Product code	Roll size
UV120	1.5 x 50m

Performance Standards

Flame Retardant grades to internationally recognised European and British Standards.

BS EN 13501 - 1

Fire classification of construction products and building elements for Euroclass classification

Technical Information

Product data	Characteristic Value
Breathable	Yes
Application	Open Facades (max 30mm)
Warranty (years)	10
UV Resistance	Long term
Colour	Black
Weight EN 695 gsm	120
Tensile Strength EN ISO 1421 N/50mm	MD >220 XD > 200
Flame Retardant test	EN 13501-1 Class E
Temperature Range °C	-40 to +80
Air layer thickness equivalent Sd or WVTR DIN EN ISO 12572 Meters ¹	Sd < 0.15 mtr
Water Penetration	W1
Water Vapour Resistance MNs/g	Sd < 0.15 mtr BS 3177
Sizes meters	1.5 x 50
Roll weight KG	9.5



Merlin House
Seven Mile Lane
Borough Green
Sevenoaks
Kent
TN15 8QY

Enquiries

0845 450 7483

International

+44 (0) 1732 882387

Fax

0845 450 7486

Email

info@fixfast.com



Certificate number 10905
ISO 9001, ISO 14001
OHSAS 18001