



RyMar Cable Flashing For Pitched Roofs

Application

- For safe penetration of roofing membranes to allow cables onto the roof

Key Features

- Pipe/elbow manufactured from Stainless Steel grade 316
- Bitumen flange for attaching to the roof membrane

RyMar Cable flashing for pitched roofs

Product Code	Base dia (mm)	Duct dia (mm)	Flange Material	Pipe Material	Duct height (mm)
RM-CF-P 32 SBS	490 dia	32	Bitumen	Stainless Steel	121



RMCF-P

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007