



RyMar[®] vent pipe cover

Vent pipe cover - insertion model

Application

- The vent pipe cover is used for the flashing of soil pipes which penetrate the roof construction and the roofing membrane

Key Features

- Manufactured from high quality stainless steel
- Systematic and secure solution
- Provides both a watertight flashing of the roofing membrane and an airtight extension of the soil pipe above the roof.
- Can be supplied with flange either for bituminous or synthetic roofing membranes.

Datasheet

Document reference: DS-RDS-IMV-7.17/01

04 ROOFTOP PRODUCTS
RyMar[®] vent pipe cover
- insertion model

RyMar® Vent pipe cover - insertion model

RyMar® Vent pipe covers - insertion model					
Code	Pipe diameters (mm)	O-ring seal diameter (mm)	Membrane attachment	To suit vent pipe OD (mm)	To suit vent pipe ID (mm)
RM-IMVENT-75-SBS	63	10	Bituminous	75	70-79
RM-IMVENT-110-SBS	90			110	96-106
RM-IMVENT-160-SBS	145	5		160	150-153
RM-IMVENT-75-PVC LT GREY	63	10	Light grey PVC	75	70-79
RM-IMVENT-110-PVC LT GREY	90			110	96-106
RM-IMVENT-160-PVC LT GREY	145	5		160	150-153
RM-IMVENT-75-PVC DK GREY	63	10	Dark grey PVC	75	70-79
RM-IMVENT-110-PVC DK GREY	90			110	96-106
RM-IMVENT-160-PVC DK GREY	145	5		160	150-153

Spigot length: 250mm

Height above membrane (not including cowl): 300mm

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007