



PaveProp™ Adjustable

Adjustable paving supports

Application

- Adjustable support pads for paving.
- Adjustable support pads for decking.

Key Features

- Adjustable paving support pad manufactured from solid polypropylene
- Support head incorporates spacing nibs to maintain consistent drainage gap between paving
- Available in six sizes providing support heights from 40mm to 1000mm
- Suitable for use with gradients up to 6°
- Provides spacing between paving slabs of 4mm

Datasheet

04 ROOFTOP PRODUCTS
PaveProp[™] Adjustable paving
supports

PaveProp™ Adjustable paving supports

Code	Height Range (mm)	Code	Height Range (mm)
PSA-1	40-56	PSA-2	50-70
PSA-3	70-110	PSA-4	110-160
PSA-5	150-210	PSA-6	200-300
PSA-7	300-400	PSA-8	400-500
PSA-9	500-600	PSA-10	600-700
PSA-11	700-800	PSA-12	800-900
PSA-13	900-1000		



Compression tolerance: Withstands in excess of 2100Kg*

PaveProp adjustable paving supports are extremely robust and strong. They offer very high compression tolerances, with the ability to withstand the compression of the most demanding of applications. These products must be installed in accordance with manufacturers recommendations.

*Certified data available on request. PSA-4 to PSA-6 have been tested according to 'Catas Procedure – Compressive Strength', certified compression strength data is available on request.

EMP7 – EMP13 have not been tested according to the same procedure, however these items comprise only components that are utilised in the EMP1 – EMP6 range.

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

