





Lightning clips

Application

• For securing lightning conductor tape for roof and wall applications

Key Features

Datasheet

Document Reference: DS-RP-LC-4.23/01

- Unique recessed rivet to eliminate damage to the membrane
- Manufactured from high quality polymer, with excellent UV repellent properties to prevent them fading and going brittle in the sun's rays
- Easy to use supplied as one piece product
- Accommodate a conductor strip up to 25mm wide x 5mm thick
- Supplied with either 100mm x 100mm membrane flange or 70mm diameter semi-rigid PVC base

04 ROOFTOP DRAINAGE StrikeClip[™] Lightning clips

StrikeClip[™] Lightning clips

Code	Flange description	Flange size (mm)	Suggested fixing centres (mm)
LC-ROUND	Semi rigid PVC	70 diameter	500
LC-ROUND-SA	As above with self-adhesive base	70 diameter	500
LC-SBS-CHARCOAL	Felt - charcoal	100 x 100	500
LC-SBS-BRINDLE	Felt - brindle	100 x 100	500
LC-PVC-LT GREY	PVC - light grey	100 x 100	500
LC-PVC-DK GREY	PVC - dark grey	100 x 100	500
LC *	N/A		1000 **

*LC type is suitable for vertical applications only as it has no membrane flange.

** up to 20m from ground level - 500mm thereafter - IEC 62305 standard.

Please contact our sales office for bespoke requirements.

Please apply pressure with a seam roller once installed to activate the bond.



LC-SBS-CHARCOAL

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0800 304 7616 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com



Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218. The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

©Fixfast August 2019. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.

LC-ROUND