

Product Description

OBEX CORTEX 0785 Primer is used to chemically prepare porous substrates prior to bonding EPDM and self-adhesive products from the OBEX CORTEX range.

Characteristics

Easy and quick installation
Fast drying and high initial resistance

Application

Stir the Primer vigorously before and during the application. If stored for a long time in cold temperatures (< 15°C), restore to room temperature.

Apply Primer over the surface with a brush to ensure the total surface is covered.

Apply the Primer using long back and forth strokes in the entire preparing zone with moderate pressure.

Continue until surface becomes grey in colour and avoid stripes and puddles. Wait until the primed surface is completely dry according to the "push-touch" test - normally around 10 minutes - before applying the OBEX CORTEX EPDM adhesive materials.

If you need more information, please contact our Technical Department.

Characteristics

Base: Synthetic rubber
Solids (%): 3,0-7,0
Specific Gravity: 0,829
Coverage: 20 sqm / 4 litre tin

Packaging/Storage/Shelf life

Packaging: 4 litre can

Storage: Store in original, unopened cans at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf life: 12 months if stored in original container is maintained at temperatures between 15°C and 25°C. Once opened, use the product within 48 hours.

Precautions

Flammable.
Keep away from sources of ignition.
DO NOT smoke when using.
Store and use the material in well-ventilated areas.
May cause sensibility by inhalation.
Refer to the Material Safety Data Sheet